



8165 E Kaiser Blvd. Anaheim, CA 92808
www.lightlaboratory.com

Report No: L121706447



Report No: L121706447 **Issue Date:** 1/11/2018

Report Prepared For: Number Eight Lighting Company
526 Portal Street, Cotati, CA 94931

Model Number: 803/K2-HI-25/DIM1-8-700 with FR-LG-P-1-WH/NL trim

Test: Photometric/Electrical Test

Standards Used: Appropriate part or all test guidelines were used for test performed:
IESNA LM79: 2008 Approved Methods for Electrical and Photometric Measurements of Solid-State Lighting Products
ANSI NEMA ANSLG C78.377: 2008 Specification of the Chromaticity of Solid State Lighting Products
ANSI C82.77:2002: Harmonic Emission Limits-Related Quality Requirements for Lighting Equipment

Description of Sample: Client submitted the sample. Received in working and undamaged condition. No modifications were necessary.

Testing Condition: Fixture is tested with no special conditions.

Sample Arrival Date: 1/2/18

Date of Tests: 1/8/18 - 1/11/18

Seasoning of Sample: No seasoning was performed in accordance with IESNA LM-79.

Equipment List

Equipment Used	Model No	Stock No	Calibration Due Date
Chroma Programmable AC Source	61604	PS-AC02	--
Yokogawa Digital Power Meter	WT210	MT-EL06-S4	1/9/19
BK PRECISION	1747	PS-DC04	1/10/19
Fluke Digital Thermometer	52K/J	MT-TP05	1/10/19
LLI Type C Goniophotometer System	RMG-C-MKII	CD-LL04-GC	--
LLI 2M Sphere	2MR97	CD-SN03-S2	--
LLI Spectroradiometer	SPR-3000	MT-SC01-S2	Before Use

*All Results in accordance to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting.

Test Summary

Manufacturer:	Number Eight Lighting Company
Model Number:	803/K2-HI-25/DIM1-8-700 with FR-LG-P-1-WH/NL trim
Driver Model Number:	IntuitiveSystems ISD-701-1000-15-D
Total Lumens:	596.26
Input Voltage (VAC/60Hz):	120.00
Input Current (Amp):	0.079
Input Power (W):	9.28
Input Power Factor:	0.98
Current ATHD @ 120V(%):	4%
Current ATHD @ 277V(%):	N/A
Efficacy:	64
Ambient Temperature (°C):	25.0
Stabilization Time (Hours):	0:40
Total Operating Time (Hours):	1:15




FIG. 1 LUMINAIRE

*All Results in accordance to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting.

Test Methods

Photometric Measurements - Goniophotometer

A Custom Light Laboratory Type C Rotating Mirror Goniophotometer was used to measure candelas(intensity) at each angle of distribution as defined by IESNA for the appropriate fixture type.

Ambient temperature is set to 25°C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25°C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

Spectral Measurements - Integrating Sphere

A Sensing Spectroradiometer SPR-3000, in conjunction with Light Laboratory 2 meter integrating sphere was used to measure chromaticity coordinates, correlated color temperature(CCT) and the color rendering index(CRI) for each sample.

Ambient temperature is set to 25°C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25°C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

Disclaimers:

This report must not be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST or any agency of Federal Government.

Report Prepared by : Joseph Shin

Test Report Released by:



Jeff Ahn
Engineering Manager

Test Report Reviewed by:



Steve Kang
Quality Assurance

**Attached are photometric data reports. Total number of pages: 9*



8165 E. Kaiser Blvd. Anaheim, CA 92808
www.lightlaboratory.com

Photometric Test Report

IES INDOOR REPORT
PHOTOMETRIC FILENAME : L121706447.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] L121706447
[TESTLAB] LIGHT LABORATORY, INC. (www.lightlaboratory.com)
[ISSUEDATE] 1/11/2018
[MANUFAC] Number Eight Lighting Company
[LUMCAT] 803/K2-HI-25/DIM1-8-700 with FR-LG-P-1-WH/NL trim
[LUMINAIRE] LED Recessed Downlight, 25° Beam Spread, 0° Aiming Angle,
[MORE] 2.75" Dia. Aperture Trim
[BALLASTCAT] IntuitiveSystems ISD-701-1000-15-D
[OTHER] INDICATING THE CANDELA VALUES ARE ABSOLUTE AND
[MORE] SHOULD NOT BE FACTORED FOR DIFFERENT LAMP RATINGS.
[INPUT] 120VAC, 9.28W
[TEST PROCEDURE] IESNA:LM-79-08

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	596
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	64
Total Luminaire Watts	9.28
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	0.46
Spacing Criterion (90-270)	0.46
Spacing Criterion (Diagonal)	0.48
Basic Luminous Shape	Circular
Luminous Length (0-180)	0.23 ft (Diameter)
Luminous Width (90-270)	0.23 ft (Diameter)
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	9883	9883	9883
55	2256	2256	2256
65	612	612	612
75	0	0	0
85	0	0	0

CANDELA TABULATION

	<u>0</u>
0.0	2078
1.0	2070
2.0	2044
3.0	2003
4.0	1947
5.0	1878
6.0	1796
7.0	1706
8.0	1609
9.0	1506
10.0	1401
12.0	1192
14.0	988
16.0	800
18.0	628
20.0	480
22.5	334
25.0	232
27.5	165
30.0	119
35.0	68
40.0	42
45.0	27
50.0	15
55.0	5
60.0	2
65.0	1
70.0	0
75.0	0
80.0	0
85.0	0
90.0	0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : L121706447.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	407.68	N.A.	68.40
0-30	522.16	N.A.	87.60
0-40	568.05	N.A.	95.30
0-60	595.27	N.A.	99.80
0-80	596.26	N.A.	100.00
0-90	596.26	N.A.	100.00
10-90	432.69	N.A.	72.60
20-40	160.36	N.A.	26.90
20-50	181.63	N.A.	30.50
40-70	28.21	N.A.	4.70
60-80	0.98	N.A.	0.20
70-80	0.00	N.A.	0.00
80-90	0.00	N.A.	0.00
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	596.26	N.A.	100.00

Total Luminaire Efficiency = N.A.%

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	163.57
10-20	244.11
20-30	114.47
30-40	45.89
40-50	21.26
50-60	5.97
60-70	0.98
70-80	0.00
80-90	0.00
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


IES INDOOR REPORT
PHOTOMETRIC FILENAME : L121706447.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0	
	RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	0
1	115	112	110	108	112	110	108	107	106	105	103	102	101	100	99	98	97	96	0
2	110	106	103	100	108	105	102	99	101	99	97	99	97	95	96	94	93	91	0
3	106	101	97	94	104	100	96	93	97	94	91	95	92	90	93	90	89	87	0
4	102	96	92	88	101	95	91	88	93	90	87	91	88	86	89	87	85	84	0
5	99	92	87	84	97	91	87	83	89	86	83	88	85	82	86	84	81	80	0
6	95	88	83	80	94	87	83	80	86	82	79	85	81	79	83	80	78	77	0
7	92	84	80	76	91	84	79	76	83	79	76	82	78	75	81	78	75	74	0
8	89	81	77	73	88	81	76	73	80	76	73	79	75	73	78	75	72	71	0
9	86	78	74	71	85	78	74	70	77	73	70	76	73	70	76	72	70	69	0
10	83	76	71	68	82	75	71	68	75	71	68	74	70	68	73	70	68	66	0

POLAR GRAPH



Maximum Candela = 2078 Located At Horizontal Angle = 0, Vertical Angle = 0
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.)

ILLUMINANCE CONE DIAGRAM: BEAM (50%)
MOUNT HEIGHT(Ft): 12

