

MPT2 – LED Monopoint Gen 2



MPT2-R

MPT2-R/S – LED INTEGRAL & REMOTE DRIVER

- 4" x 3/8" deep canopy
- 6-1/4" Overall length x 2-3/8" diameter
- Optional 12", 18", & 24" overall lengths
- 92+ CRI 3000K white LED with three output options: 630, 890, and 1100 lumens delivered at 9, 15, and 20 watts
- 97+ CRI 3000-1800K warm dimming LED delivers up to 880 lumens at 15 watts.
- 2016 CA JA8 Compliant
- Rotates 320° and tilts 110°
- Three interchangeable beam spreads (15°, 25°, and 40°)
- Accepts up to three optical accessories
- Five interchangeable beam enhancing lenses
- Three interchangeable color filtering lenses
- Three integral dimming driver options:
1% Triac/ELV, 1% 0-10v, 0.1% Triac/ELV
- Two remote dimming driver options:
1% Lutron Triac & 1% Lutron EcoSystem
- Standard Aluminum with WH, BK, SA, & OB finishes



MPT2-S



MPT2-R-RT

MPT2-R/S-RT – LED REMOTE DRIVER

- 2-1/2" x 3/8" deep canopy
- 6-1/4" Overall length x 2-3/8" diameter
- 92+ CRI 3000K white LED with three output options: 630, 890, and 1100 lumens delivered at 9, 15, and 20 watts
- 97+ CRI 3000-1800K warm dimming LED delivers up to 875 lumens at 15 watts.
- 2016 CA JA8 Compliant
- Rotates 320° and tilts 110°
- Three interchangeable beam spreads (15°, 25°, and 40°)
- Accepts up to three optical accessories
- Five interchangeable beam enhancing lenses
- Three interchangeable color filtering lenses
- Two remote dimming driver options:
1% Lutron Triac & 1% Lutron EcoSystem
- Remote driver can be located up to 100' from fixture
- Standard Aluminum with WH, BK, SA, & OB finishes



MPT2-S-RT



526 Portal Street
Cotati, CA 94931
USA

P 707.794.0888
F 707.795-4379

www.8lighting.com

All No. 8 Lighting fixtures and components are UL/CSA listed. No. 8 Lighting trims and lamp modules are protected by one or more U.S. Patents. No. 8 Lighting reserves the right to change details of design, materials, and finish.

© 2019 No. 8 Lighting



06/2019