

No. 8 Lighting **LED** Product Comparison Chart

	800 SERIES	400 SERIES	200 SERIES
IC-RATED	✓	✓	w/ IC-CP Housing Option
CHICAGO PLENUM	✓	w/ CP Housing Option	w/ IC-CP Housing Option
REMODEL	—	✓	—
2019 CA JAB COMPLIANT	✓	✓	✓
LED OPTIONS	<ul style="list-style-type: none"> • 3000K 92+ CRI White • 4500 -2200K 92+ CRI Tunable White • 3000 -1800K 97+ CRI Warm Dim • 2800 -2200K 95+ CRI Warm Dim 	<ul style="list-style-type: none"> • 3000K 92+ CRI White • 3000 -1800K 97+ CRI Warm Dim • 2800 -2200K 95+ CRI Warm Dim 	<ul style="list-style-type: none"> • 2700K/3000K/3500K/4000K 92+ CRI White • 3000 -1800K 97+ CRI Warm Dim • 2800 -2200K 95+ CRI Warm Dim
DELIVERED LUMENS	<ul style="list-style-type: none"> • Low Output = 821lm @ 9.7w • Standard Output = 1087lm @ 14.2w • High Output = 1144lm @ 20.3w 	<ul style="list-style-type: none"> • Standard Output = 1077lm @ 14w 	<ul style="list-style-type: none"> • Standard Output = 1265lm @ 14w
LAMP MODULE OPTIONS	<ul style="list-style-type: none"> • Fixed Downlight • Adjustable Accent (0°-45°) • Adjustable Wall Wash • Mirror Reflector (45°-90°) 	<ul style="list-style-type: none"> • Adjustable Accent (0°-35°) • Adjustable Wall Wash 	<ul style="list-style-type: none"> • Fixed Downlight • Adjustable Accent (0°-30°) • Fixed Wall Wash
OPTIC OPTIONS	<ul style="list-style-type: none"> • 10°, 15°, 25°, and 40° • Beam enhancing lenses: Narrow, Medium, Wide, Extra Wide, and Linear Spread • Color filtering lenses: 2400K, 2700K, and 3500°K 	<ul style="list-style-type: none"> • 10°, 15°, 25°, and 40° • Beam enhancing lenses: Narrow, Medium, Wide, Extra Wide, and Linear Spread • Color filtering lenses: 2400K, 2700K, and 3500°K 	<ul style="list-style-type: none"> • 15°, 25°, 40°, and 60° • Beam enhancing lenses: Narrow, Medium, Wide, Extra Wide, and Linear Spread
DIMMING OPTIONS	<ul style="list-style-type: none"> • 0.1% Forward/Reverse Phase (standard) • 1% Forward/Reverse Phase • 1% 0 -10v • EldoLED 1% 0 -10v • EldoLED 1% DALI • EldoLED 0.1% DALI 2-Channel (tunable white) • EldoLED 0.1% DMX 4-Channel (tunable white) • EldoLED 0.1% 0-10v 2-Channel (tunable white) • Lutron 1% Forward Phase • Lutron 1% EcoSystem • Lutron 0.1% EcoSystem • Lutron 1% T-Series 2-Channel (tunable white) 	<ul style="list-style-type: none"> • 1% Forward/Reverse Phase (standard) • 0.1% Forward/Reverse Phase • 1% 0 -10v • EldoLED 1% 0-10v • EldoLED 1% DALI • Lutron 1% Forward Phase (integral and remote) • Lutron 1% EcoSystem (integral and remote) • Lutron 0.1% EcoSystem 	<ul style="list-style-type: none"> • 5% Forward/Reverse Phase (standard) • 5% 0-10v • 1% Forward/Reverse Phase • 1% 0-10v • EldoLED 1% 0-10v • EldoLED 1% DALI • Lutron 1% Forward Phase • Lutron 1% EcoSystem • Lutron 0.1% EcoSystem
TRIM OPTIONS	<ul style="list-style-type: none"> • 1.75" and 2.75" Aperture • Square and Round • Flanged and Flangeless • Flat, Bevel, and Inset • White, Polished Nickel, Satin Nickel, Oil-Rubbed Bronze, and Black 	<ul style="list-style-type: none"> • 2" Aperture • Square and Round • Flanged and Flangeless • Flat and Bevel • White and Oil-Rubbed Bronze 	<ul style="list-style-type: none"> • 1.875", 2.25", and 2-3/4" (wall wash) Aperture • Square and Round • Flanged and Flangeless • Flat, Bevel, and Wall Wash • White and Oil-Rubbed Bronze
WET LOCATION	✓	✓	✓
WARRANTY	5 Year Limited	5 Year Limited	5 Year Limited



526 Portal Street
Cotati, CA 94931
USA

P 707.794.0888
F 707.795.4379

www.8lighting.com

All No. 8 Lighting fixtures and components are UL/CSA listed. No. 8 Lighting trims and lamp modules are protected by one or more U.S. Patents. No. 8 Lighting reserves the right to change details of design, materials, and finish.

© 2020 No. 8 Lighting



09/2020