

## Photometric / Colorimetric / Electric Report

Fixture Model:

200-HD-R-HI3500-60-EL1-2-HD-FLR-2-NIC-30d

Trim Model:

FLR-2-WH

Date:

8/19/2022



Light efficiency:

27 Lumen/Watt

Light quality:

CRI: 94.5

Color temperature:

3523 K

CIE 1931:

x: 0.403  
y: 0.386


Output: 696 lm

Peak: 2008 cd



Power: 26.2 W

PF: 0.98


Spectra:




## Color Details



**TM-30: 90.9**



**CRI: 94.5 (R1-R8)**



**CRI R Values:**

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
95.7	98.7	98.4	93.6	94.4	95.8	92.9	86.5	70.1	94.9	94.2	77.5	97.1	99.0	93.0


**TM30 C Values:**

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
90.7	93.5	93.3	93.3	92.2	96.5	92.0	93.7	89.8	85.1	86.9	90.8	92.9	89.2	88.9	87.9

**CQS Q values:**

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
90.7	97.5	89.8	87.1	90.1	92.6	95.0	95.2	99.3	96.4	95.0	94.6	94.7	91.1	91.2

**CQS: 92.6**



**Color Parameters:**

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3523 K	94.5	70.1	90.9	97.8	92.6	0.403	0.386	0.236	0.339	-0.0017

# TM-30 Details







**Rf 90.9**

Fidelity index Rf

**Rg 97.8**

Gamut index Rg

Hue Bin	R <sub>f</sub>	Shifts (%)	
		Chroma	Hue
1	91	-4%	1%
2	93	-2%	2%
3	93	-1%	3%
4	93	-2%	0%
5	92	-5%	0%
6	97	-1%	0%
7	92	-5%	2%
8	94	-3%	3%
9	90	-2%	7%
10	85	0%	10%
11	87	4%	8%
12	91	5%	1%
13	93	2%	-5%
14	89	4%	-8%
15	89	-1%	-6%
16	88	-2%	-6%



## Aiming Angle

