

DIMMER COMPATIBILITY

800 SERIES

DRIVER MODELS: DIM1-8-1000/1000-WD/1400

LED MODELS: HI, HI-2, WD/WD-2



www.8lighting.com

No.8 Lighting Driver Model	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Recommended Trim Settings		Adjust (Vantage Only)	Dimming Range	
								High-End (%)	Low-End (%)		High-End (%)	Low-End (%)
DIM1-8												
DIM1-8-1400	HI	Crestron	Cameo Express	CLW-DELVE-X-E	120	Reverse Phase	Wallbox/System	80.0	3.0		100.0%	4.0%
DIM1-8-1400	HI	Crestron	Cameo Express	CLW-DELVE-X-P	120	Reverse Phase	Wallbox/System	80.0	3.0		100.0%	4.0%
DIM1-8-1000	HI	Crestron	Cameo Express Wireless	CLW-DIMEX-E	120	Forward Phase	Wallbox/System	75.0	3.0		100.0%	3.0%
DIM1-8-1000-WD	WD/WD-2							75.0	5.0		100.0%	1.0%
DIM1-8-1400	HI							75.0	10.0		100.0%	8.0%
DIM1-8-1000	HI	Crestron	Cameo Wireless	CLW-DIMEX-P	120	Forward Phase	Wallbox/System	75.0	3.0		100.0%	3.0%
DIM1-8-1000-WD	WD/WD-2							75.0	5.0		100.0%	1.0%
DIM1-8-1400	HI							75.0	10.0		100.0%	8.0%
DIM1-8-1000	HI	Crestron	Cameo Express Wireless	CLW-DIMSWEX-E	120	Forward Phase	Wallbox/System	75.0	3.0		100.0%	3.0%
DIM1-8-1000-WD	WD/WD-2							75.0	5.0		100.0%	1.0%
DIM1-8-1400	HI							75.0	10.0		100.0%	8.0%
DIM1-8-1000	HI	Crestron	Cameo Wireless	CLW-DIMSWEX-P	120	Forward Phase	Wallbox/System	75.0	3.0		100.0%	3.0%
DIM1-8-1000-WD	WD/WD-2							75.0	5.0		100.0%	1.0%
DIM1-8-1400	HI							75.0	10.0		100.0%	8.0%
DIM1-8-1000	HI	Crestron	Cameo Wireless	CLW-DIMUEX-P	120	Forward or Reverse Phase	Wallbox/System	80.0	10.0		100.0%	1.0%
DIM1-8-1000-WD	WD/WD-2							85.0	20.0		100.0%	1.0%
DIM1-8-1400	HI							80.0	7.0		100.0%	1.0%
DIM1-8-1000	HI	Crestron		CLX-1DIMU4	120	Forward or Reverse Phase	Residential/Commercial System	80.0	10.0		100.0%	1.0%
DIM1-8-1000-WD	WD/WD-2							85.0	20.0		100.0%	1.0%
DIM1-8-1400	HI							80.0	15.0		100.0%	5.0%
DIM1-8-1000	HI	Crestron		CLX-2DIMU8	120	Forward or Reverse Phase	Residential/Commercial System	80.0	10.0		100.0%	1.0%
DIM1-8-1000-WD	WD/WD-2							85.0	20.0		100.0%	1.0%
DIM1-8-1400	HI							80.0	15.0		100.0%	5.0%
DIM1-8-1000	HI	Crestron	Wireless Horizon	HZ-DIMEX SERIES	120	Forward Phase	Wallbox/System	80.0	10.0		100.0%	1.0%
DIM1-8-1000-WD	WD/WD-2							85.0	15.0		100.0%	1.0%
DIM1-8-1400	HI							85.0	15.0		100.0%	5.0%
DIM1-8-1000	HI	Crestron	Wireless Horizon	HZ-DIMUEX SERIES	120	Forward or Reverse Phase	Wallbox/System	80.0	10.0		100.0%	1.0%
DIM1-8-1000-WD	WD/WD-2							85.0	15.0		100.0%	1.0%
DIM1-8-1400	HI							85.0	15.0		100.0%	5.0%
DIM1-8-1000	HI	Crestron		P-DIMEX	120	Forward Phase	Wallbox/System	75.0	3.0		100.0%	3.0%
DIM1-8-1000-WD	WD/WD-2							75.0	5.0		100.0%	1.0%
DIM1-8-1400	HI							75.0	10.0		100.0%	8.0%
DIM1-8-1000	HI	Crestron	Zum Wireless	ZUMMESH-DELV	120	Reverse Phase	Wallbox/System	80.0	12.0		100.0%	1.0%
DIM1-8-1000-WD	WD/WD-2							80.0	25.0		100.0%	1.0%
DIM1-8-1400	HI							85.0	11.0		100.0%	1.0%
DIM1-8-1000	HI	Crestron	Zum Wireless	ZUMMESH-DIM	120	Forward Phase	Wallbox/System	80.0	12.0		100.0%	6.0%
DIM1-8-1000-WD	WD/WD-2							80.0	25.0		100.0%	2.0%
DIM1-8-1400	HI							85.0	15.0		100.0%	6.0%
DIM1-8-1000	HI	Crestron	Zum Wireless	ZUMMESH-EXP-16A-DIMU	120	Forward or Reverse Phase	Wallbox/System	75.0	7.0		100.0%	1.0%
DIM1-8-1000-WD	WD/WD-2							85.0	20.0		100.0%	1.0%
DIM1-8-1400	HI							80.0	7.0		100.0%	1.0%
DIM1-8-1000	HI-2	Lutron	Caseta	PD-5NE	120	Reverse Phase	Wallbox	High & Low-End Trim Required			99.9%	0.1%
DIM1-8-1000	HI							100.0%	0.4%			
DIM1-8-1000-WD	WD/WD-2							100.0%	0.0%			
DIM1-8-1400	HI		100.0%	0.1%								
DIM1-8-1000	HI-2	Lutron	Caseta	PD-6WCL	120	Forward Phase	Wallbox	High & Low-End Trim Required			99.4%	0.1%
DIM1-8-1000	HI							99.2%	0.1%			
DIM1-8-1000-WD	WD/WD-2							95.2%	0.0%			
DIM1-8-1000	HI-2	Lutron	Caseta	PD-10NXD	120	Forward Phase	Wallbox	High & Low-End Trim Required			99.6%	0.3%
DIM1-8-1000	HI							99.0%	0.9%			
DIM1-8-1000-WD	WD/WD-2							95.1%	0.0%			
DIM1-8-1400	HI		99.8%	0.9%								
DIM1-8-1000	HI-2	Lutron	Diva	DVCL-253PH	120	Forward Phase	Wallbox	High & Low-End Trim Required			98.9%	0.4%
DIM1-8-1000	HI							99.3%	0.6%			
DIM1-8-1000-WD	WD/WD-2							98.4%	4.3%			
DIM1-8-1400	HI		100.0%	0.3%								
DIM1-8-1000	HI-2	Lutron	Grafik Eye 3000	GRX-3506	120	Forward Phase	Residential/Commercial System	High & Low-End Trim Required			98.6%	0.8%
DIM1-8-1000	HI							94.3%	5.3%			
DIM1-8-1000-WD	WD/WD-2							93.4%	0.1%			
DIM1-8-1400	HI		99.6%	1.0%								
DIM1-8-1000	HI-2	Lutron	Grafik Eye QS	QSGRJ-4P	120	Forward Phase	Residential/Commercial System	79.0	1.0		98.1%	1.1%
DIM1-8-1000	HI							81.0	8.0		98.5%	0.8%
DIM1-8-1000-WD	WD/WD-2							100.0	8.0		99.3%	0.2%
DIM1-8-1400	HI		79.0	8.0		98.8%	1.0%					
DIM1-8-1000	HI-2	Lutron	Homeworks QS	HQRA-PRO	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			99.0%	0.3%
DIM1-8-1000	HI							99.1%	0.2%			
DIM1-8-1000-WD	WD/WD-2							98.3%	0.1%			
DIM1-8-1400	HI		99.6%	1.2%								
DIM1-8-1000	HI-2	Lutron	Homeworks QS	HQRA-PRO	120	Reverse Phase	Wallbox/System	High & Low-End Trim Required			100.0%	0.2%
DIM1-8-1000	HI							100.0%	0.3%			
DIM1-8-1000-WD	WD/WD-2							89.1%	0.1%			
DIM1-8-1400	HI		100.0%	0.2%								

No.8 Lighting Driver Model	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Recommended Trim Settings		Adjust (Vantage Only)	Dimming Range	
								High-End (%)	Low-End (%)		High-End (%)	Low-End (%)
DIM1-8 (Continued)												
DIM1-8-1000	HI-2	Lutron	Homeworks QS	HQRD-10ND	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			99.7%	1.3%
DIM1-8-1000	HI										99.3%	3.0%
DIM1-8-1000-WD	WD/WD-2										98.0%	0.1%
DIM1-8-1400	HI	Lutron	Homeworks QSX	LQSE-4A-120-D*	120	Forward Phase	Residential/ Commercial System				100.0%	2.4%
DIM1-8-1000*	HI-2										97.7%	0.4%
DIM1-8-1000*	HI										97.9%	0.3%
DIM1-8-1000-WD*	WD/WD-2										99.4%	0.1%
DIM1-8-1400*	HI										98.9%	0.6%
DIM1-8-1000*	HI-2	Lutron	Homeworks QSX	LQSE-4A-120-D*	120	Reverse Phase	Residential/ Commercial System				81.0	10.0
DIM1-8-1000*	HI										85.0	10.0
DIM1-8-1000-WD*	WD/WD-2										98.0	38.0
DIM1-8-1400*	HI										82.0	12.0
DIM1-8-1000	HI-2										80.0	1.0
DIM1-8-1000	HI	Lutron	Homeworks QSX	LQSE-4A5-120-D	120	Forward Phase	Residential/ Commercial System				80.0	1.0
DIM1-8-1000	HI										97.9%	0.3%
DIM1-8-1000-WD	WD										97.0	9.0
DIM1-8-1400	HI										97.9%	0.6%
DIM1-8-1000	HI-2										82.0	12.0
DIM1-8-1000	HI	Lutron	Homeworks QSX	LQSE-4A5-120-D	120	Reverse Phase	Residential/ Commercial System				85.0	12.0
DIM1-8-1000	HI										100.0%	0.2%
DIM1-8-1000-WD	WD/WD-2										100.0	38.0
DIM1-8-1400	HI										100.0%	0.1%
DIM1-8-1000	HI-2										83.0	12.0
DIM1-8-1000	HI-2	Lutron	Maestro	MA-PRO-XX	120	Forward Phase	Wallbox	High & Low-End Trim Required			99.4%	0.2%
DIM1-8-1000	HI										98.3%	1.3%
DIM1-8-1000-WD	WD/WD-2										98.3%	0.1%
DIM1-8-1400	HI	Lutron	Maestro	MA-PRO-XX	120	Reverse Phase	Wallbox	High & Low-End Trim Required			99.7%	6.4%
DIM1-8-1000	HI-2										94.0%	0.3%
DIM1-8-1000	HI										90.7%	0.1%
DIM1-8-1000-WD	WD/WD-2										91.0%	0.1%
DIM1-8-1400	HI										85.6%	0.1%
DIM1-8-1000	HI-2	Lutron	Maestro	MACL-153M	120	Forward Phase	Wallbox	High & Low-End Trim Required			99.5%	0.1%
DIM1-8-1000	HI										98.7%	2.0%
DIM1-8-1000-WD	WD/WD-2										96.7%	0.1%
DIM1-8-1400	HI										99.6%	0.1%
DIM1-8-1000	HI-2										100.0%	0.1%
DIM1-8-1000	HI	Lutron	Maestro	MRF2-6ELV-120	120	Reverse Phase	Wallbox	High & Low-End Trim Required			100.0%	0.1%
DIM1-8-1000	HI										100.0%	0.1%
DIM1-8-1000-WD	WD/WD-2										90.0%	0.1%
DIM1-8-1400	HI										100.0%	0.1%
DIM1-8-1000	HI-2										98.9%	0.4%
DIM1-8-1000	HI	Lutron	Maestro	MRF2-6ND-120	120	Forward Phase	Wallbox	High & Low-End Trim Required			98.2%	1.1%
DIM1-8-1000	HI										98.3%	0.0%
DIM1-8-1000-WD	WD/WD-2										99.2%	3.9%
DIM1-8-1400	HI										100.0%	0.1%
DIM1-8-1000	HI-2										100.0%	0.1%
DIM1-8-1000	HI	Lutron	Radio RA 2	RRD-6NA	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			99.0%	0.5%
DIM1-8-1000	HI										90.3%	0.0%
DIM1-8-1000-WD	WD/WD-2										100.0%	0.9%
DIM1-8-1400	HI										99.0%	0.7%
DIM1-8-1000	HI-2										100.0%	0.1%
DIM1-8-1000	HI	Lutron	Radio RA 2	RRD-6NA	120	Reverse Phase	Wallbox/System	High & Low-End Trim Required			98.2%	0.1%
DIM1-8-1000	HI										100.0%	0.3%
DIM1-8-1000-WD	WD/WD-2										100.0%	0.1%
DIM1-8-1400	HI										99.3%	0.4%
DIM1-8-1000	HI-2										98.9%	4.6%
DIM1-8-1000	HI	Lutron	Radio RA 2	RRD-10ND	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			98.1%	0.0%
DIM1-8-1000	HI										100.0%	1.2%
DIM1-8-1000	HI-2										99.0%	0.3%
DIM1-8-1000	HI										98.8%	0.2%
DIM1-8-1000-WD	WD/WD-2										98.4%	0.0%
DIM1-8-1000	HI-2	Lutron	Radio RA 2	RRD-PRO	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			100.0%	0.4%
DIM1-8-1000	HI										100.0%	0.1%
DIM1-8-1000-WD	WD/WD-2										88.8%	0.1%
DIM1-8-1400	HI										100.0%	0.2%
DIM1-8-1000	HI										79.5	4.0
DIM1-8-1000	HI-2	Vantage	ScenePoint		120	Forward Phase	Residential System				81.0	9.0
DIM1-8-1000	HI										74.2	5.0
DIM1-8-1000-WD	WD/WD-2										75.0	2.5
DIM1-8-1400	HI										100.0%	3.2%
DIM1-8-1000	HI										77.5	7.0
DIM1-8-1000	HI	Vantage	SDM12-EM		120	Forward Phase	Residential System				70.0	2.5
DIM1-8-1000	HI										77.5	3.0
DIM1-8-1000-WD	WD/WD-2										100.0%	1.2%
DIM1-8-1400	HI										95.0%	2.8%
DIM1-8-1000	HI										77.5	3.0
DIM1-8-1000	HI	Vantage	UDM-FWD		120	Forward Phase	Residential System				79.5	7.0
DIM1-8-1000	HI										73.5	2.5
DIM1-8-1000-WD	WD/WD-2										100.0%	0.9%
DIM1-8-1400	HI										95.0%	1.8%
DIM1-8-1000	HI										82.5	9.0
DIM1-8-1000	HI	Vantage	UDM-REV		120	Reverse Phase	Residential System				87.5	22.0
DIM1-8-1000	HI										25	95.3%
DIM1-8-1000-WD	WD/WD-2										79.0	9.5
DIM1-8-1400	HI										40	95.0%
DIM1-8-1000	HI										80.3	4.5
DIM1-8-1000	HI	Vantage	UDS-F		120	Forward Phase	Wallbox/System				82.4	9.0
DIM1-8-1000	HI										100	94.8%
DIM1-8-1000-WD	WD/WD-2										76.5	3.5
DIM1-8-1400	HI										100	94.6%
DIM1-8-1000	HI										80.5	10.0
DIM1-8-1000	HI	Vantage	UDS-R		120	Reverse Phase	Wallbox/System				86.0	21.0
DIM1-8-1000	HI										25	95.2%
DIM1-8-1000-WD	WD/WD-2										77.5	9.0
DIM1-8-1400	HI										50	94.8%
DIM1-8-1000	HI										77.5	9.0

Dimmer compatibility testing performed using 120V/60Hz supply.

Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.

The design, specification, or performance of compatible dimmers is subject to change without notice.

* Maximum of four (4) drivers per output with Lutron LQSE-4A-120-D.

For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93001-1 - 01/2023

DIMMER COMPATIBILITY
800 SERIES
DRIVER MODELS: PR1-8-1000/1400
LED MODELS: HI, HI-2



www.8lighting.com

No.8 Lighting Driver Model	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Recommended Trim Settings		Adjust (Vantage Only)	Dimming Range	
								High-End (%)	Low-End (%)		High-End (%)	Low-End (%)
PR1-8												
PR1-8-1000	HI	Creston	Cameo Express Wireless	CLW-DIMEX-E	120	Forward Phase	Wallbox/System	75.0	3.0		100.0%	3.0%
PR1-8-1400	HI							75.0	10.0		100.0%	7.0%
PR1-8-1000	HI	Creston	Cameo Wireless	CLW-DIMEX-P	120	Forward Phase	Wallbox/System	75.0	3.0		100.0%	3.0%
PR1-8-1400	HI							75.0	10.0		100.0%	7.0%
PR1-8-1000	HI	Creston	Cameo Express Wireless	CLW-DIMSWEX-E	120	Forward Phase	Wallbox/System	75.0	3.0		100.0%	3.0%
PR1-8-1400	HI							75.0	10.0		100.0%	7.0%
PR1-8-1000	HI	Creston	Cameo Wireless	CLW-DIMSWEX-P	120	Forward Phase	Wallbox/System	75.0	3.0		100.0%	3.0%
PR1-8-1400	HI							75.0	10.0		100.0%	7.0%
PR1-8-1000	HI	Creston	Cameo Wireless	CLW-DIMUEX-P	120	Forward or Reverse Phase	Wallbox/System	80.0	3.0		100.0%	1.0%
PR1-8-1400	HI							80.0	1.0		100.0%	1.0%
PR1-8-1000	HI	Creston		CLX-1DIMU4	120	Forward or Reverse Phase	Residential/Commercial System	80.0	5.0		100.0%	1.0%
PR1-8-1400	HI							80.0	25.0		100.0%	5.0%
PR1-8-1000	HI	Creston		CLX-2DIMU8	120	Forward or Reverse Phase	Residential/Commercial System	80.0	5.0		100.0%	1.0%
PR1-8-1400	HI							80.0	25.0		100.0%	5.0%
PR1-8-1000	HI	Creston	Wireless Horizon	HZ-DIMEX SERIES	120	Forward Phase	Wallbox/System	80.0	10.0		100.0%	1.0%
PR1-8-1400	HI							80.0	3.0		100.0%	1.0%
PR1-8-1000	HI	Creston	Wireless Horizon	HZ-DIMUEX SERIES	120	Forward or Reverse Phase	Wallbox/System	80.0	10.0		100.0%	2.0%
PR1-8-1400	HI							80.0	3.0		100.0%	1.0%
PR1-8-1000	HI	Creston		P-DIMEX	120	Forward Phase	Wallbox/System	75.0	3.0		100.0%	3.0%
PR1-8-1400	HI							75.0	10.0		100.0%	7.0%
PR1-8-1000	HI	Creston	Zum Wireless	ZUMMESH-DELV	120	Reverse Phase	Wallbox/System	80.0	10.0		100.0%	1.0%
PR1-8-1400	HI							85.0	9.0		100.0%	1.0%
PR1-8-1000	HI	Creston	Zum Wireless	ZUMMESH-DIM	120	Forward Phase	Wallbox/System	80.0	20.0		100.0%	8.0%
PR1-8-1400	HI							80.0	15.0		100.0%	5.0%
PR1-8-1000	HI	Creston	Zum Wireless	ZUMMESH-EXP-16A-DIMU	120	Forward or Reverse Phase	Wallbox/System	80.0	15.0		100.0%	3.0%
PR1-8-1400	HI							80.0	14.0		100.0%	1.0%
PR1-8-1000	HI-2	Lutron	Caseta	PD-5NE	120	Reverse Phase	Wallbox	High & Low-End Trim Required			99.9%	0.3%
PR1-8-1000	HI							99.9%	0.1%			
PR1-8-1400	HI	Lutron	Caseta	PD-6WCL	120	Forward Phase	Wallbox	High & Low-End Trim Required			100.0%	0.3%
PR1-8-1000	HI							100.0%	0.4%			
PR1-8-1000	HI-2	Lutron	Caseta	PD-10NND	120	Forward Phase	Wallbox	High & Low-End Trim Required			100.0%	0.1%
PR1-8-1000	HI							100.0%	0.6%			
PR1-8-1400	HI	Lutron	Diva	DVCL-253PH	120	Forward Phase	Wallbox	High & Low-End Trim Required			100.0%	0.6%
PR1-8-1000	HI-2							100.0%	0.4%			
PR1-8-1000	HI	Lutron	Grafik Eye 3000	GRX-3506	120	Forward Phase	Residential/Commercial System	High & Low-End Trim Required			100.0%	0.3%
PR1-8-1400	HI							100.0%	0.8%			
PR1-8-1000	HI-2	Lutron	Grafik Eye QS	QSGRJ-4P	120	Forward Phase	Residential/Commercial System	79.0	1.0		100.0%	0.5%
PR1-8-1000	HI							80.0	5.0		100.0%	1.1%
PR1-8-1400	HI	Lutron	Homeworks QS	HQRA-PRO	120	Forward Phase	Wallbox/System	79.0	5.0		100.0%	0.6%
PR1-8-1000	HI-2							100.0%	0.6%			
PR1-8-1000	HI	Lutron	Homeworks QS	HQRA-PRO	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			100.0%	0.5%
PR1-8-1400	HI							100.0%	0.8%			
PR1-8-1000	HI-2	Lutron	Homeworks QS	HQRA-PRO	120	Reverse Phase	Wallbox/System	High & Low-End Trim Required			100.0%	0.6%
PR1-8-1000	HI							100.0%	0.4%			
PR1-8-1400	HI	Lutron	Homeworks QS	HQRD-10ND	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			100.0%	0.4%
PR1-8-1000	HI-2							99.7%	0.6%			
PR1-8-1000	HI	Lutron	Homeworks QS	HQRD-10ND	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			100.0%	1.7%
PR1-8-1400	HI							100.0%	4.5%			
PR1-8-1000*	HI-2	Lutron	Homeworks QSX	LQSE-4A-120-D*	120	Forward Phase	Residential/Commercial System	80.0	1.0		100.0%	0.7%
PR1-8-1000*	HI							79.0	1.0		100.0%	0.6%
PR1-8-1400*	HI	Lutron	Homeworks QSX	LQSE-4A-120-D*	120	Reverse Phase	Residential/Commercial System	78.0	1.0		100.0%	0.9%
PR1-8-1000*	HI-2							84.0	5.0		100.0%	0.2%
PR1-8-1000*	HI	Lutron	Homeworks QSX	LQSE-4A-120-D*	120	Forward Phase	Residential/Commercial System	83.0	5.0		100.0%	0.2%
PR1-8-1400*	HI							85.0	4.0		100.0%	0.2%
PR1-8-1000	HI-2	Lutron	Homeworks QSX	LQSE-4A5-120-D	120	Forward Phase	Residential/Commercial System	80.0	2.0		100.0%	0.7%
PR1-8-1000	HI							80.0	1.0		100.0%	0.6%
PR1-8-1400	HI	Lutron	Homeworks QSX	LQSE-4A5-120-D	120	Reverse Phase	Residential/Commercial System	80.0	1.0		100.0%	0.9%
PR1-8-1000	HI-2							84.0	5.0		100.0%	0.3%
PR1-8-1000	HI	Lutron	Homeworks QSX	LQSE-4A5-120-D	120	Reverse Phase	Residential/Commercial System	84.0	6.0		100.0%	0.3%
PR1-8-1400	HI							85.0	4.0		100.0%	0.2%
PR1-8-1000	HI-2	Lutron	Maestro	MA-PRO-XX	120	Forward Phase	Wallbox	High & Low-End Trim Required			100.0%	0.5%
PR1-8-1000	HI							100.0%	0.4%			
PR1-8-1400	HI	Lutron	Maestro	MA-PRO-XX	120	Reverse Phase	Wallbox	High & Low-End Trim Required			100.0%	4.4%
PR1-8-1000	HI-2							100.0%	0.5%			
PR1-8-1000	HI	Lutron	Maestro	MA-PRO-XX	120	Reverse Phase	Wallbox	High & Low-End Trim Required			92.1%	0.5%
PR1-8-1400	HI							100.0%	0.2%			

No.8 Lighting Driver Model	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Recommended Trim Settings		Adjust (Vantage Only)	Dimming Range	
								High-End (%)	Low-End (%)		High-End (%)	Low-End (%)
PR1-8 (Continued)												
PR1-8-1000	HI-2	Lutron	Maestro	MACL-153M	120	Forward Phase	Wallbox	High & Low-End Trim Required			100.0%	0.3%
PR1-8-1000	HI										100.0%	0.8%
PR1-8-1400	HI										100.0%	0.1%
PR1-8-1000	HI-2	Lutron	Maestro	MRF2-6ELV-120	120	Reverse Phase	Wallbox	High & Low-End Trim Required			100.0%	0.3%
PR1-8-1000	HI										100.0%	0.3%
PR1-8-1400	HI										100.0%	0.1%
PR1-8-1000	HI-2	Lutron	Maestro	MRF2-6ND-120	120	Forward Phase	Wallbox	High & Low-End Trim Required			100.0%	0.7%
PR1-8-1000	HI										100.0%	1.6%
PR1-8-1400	HI										100.0%	1.7%
PR1-8-1000	HI-2	Lutron	Radio RA 2	RRD-6NA	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			100.0%	0.4%
PR1-8-1000	HI										100.0%	0.3%
PR1-8-1400	HI										100.0%	2.3%
PR1-8-1000	HI-2	Lutron	Radio RA 2	RRD-6NA	120	Reverse Phase	Wallbox/System	High & Low-End Trim Required			100.0%	1.1%
PR1-8-1000	HI										100.0%	1.0%
PR1-8-1400	HI										100.0%	0.1%
PR1-8-1000	HI-2	Lutron	Radio RA 2	RRD-10ND	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			100.0%	0.7%
PR1-8-1000	HI										100.0%	4.1%
PR1-8-1400	HI										100.0%	2.0%
PR1-8-1000	HI-2	Lutron	Radio RA 2	RRD-PRO	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			100.0%	0.4%
PR1-8-1000	HI										100.0%	0.6%
PR1-8-1400	HI										100.0%	4.1%
PR1-8-1000	HI-2	Lutron	Radio RA 2	RRD-PRO	120	Reverse Phase	Wallbox/System	High & Low-End Trim Required			100.0%	0.5%
PR1-8-1000	HI										100.0%	0.5%
PR1-8-1400	HI										100.0%	0.4%
PR1-8-1000	HI	Vantage		ScenePoint	120	Forward Phase	Wallbox	78.5	3.5	85	94.9%	1.9%
PR1-8-1400	HI							73.5	4.0	95	95.1%	1.8%
PR1-8-1000	HI							75.4	2.0	85	95.3%	1.2%
PR1-8-1400	HI	Vantage		SDM12-EM	120	Forward Phase	Wallbox	68.0	2.5	95	94.9%	2.4%
PR1-8-1000	HI							78.2	3.0	85	94.9%	1.5%
PR1-8-1400	HI							72.0	3.5	100	94.9%	2.3%
PR1-8-1000	HI	Vantage		UDM-FWD	120	Forward Phase	Wallbox	84.5	6.5	40	95.4%	1.6%
PR1-8-1400	HI							80.4	6.8	40	95.1%	2.2%
PR1-8-1000	HI							81.0	3.5	85	95.0%	1.5%
PR1-8-1000	HI	Vantage		UDS-F	120	Forward Phase	Wallbox/System	75.5	4.0	90	95.1%	1.4%
PR1-8-1400	HI							82.4	4.5	40	94.8%	1.2%
PR1-8-1000	HI							79.2	4.7	40	95.0%	2.5%

Dimmer compatibility testing performed using 120V/60Hz supply.

Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.

The design, specification, or performance of compatible dimmers is subject to change without notice.

* Maximum of four (4) drivers per output with Lutron LQSE-4A-120-D.

For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93001-2 - 01/2023

DIMMER COMPATIBILITY

800 SERIES

DRIVER MODELS: LU1-8-1000/1400/1000-WD

LED MODELS: HI, HI-2, WD/WD-2



www.8lighting.com

No.8 Lighting Driver Model	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Recommened Trim Settings		Adjust (Vantage Only)	Dimming Range		
								High-End (%)	Low-End (%)		High-End (%)	Low-End (%)	
LU1-8													
LU1-8-1000	HI	Crestron	Cameo Express Wireless	CLW-DIMEX-E	120	Forward Phase	Wallbox/System	70.0	19.0		100.0%	1.0%	
LU1-8-1000-WD	WD/WD-2							70.0	19.0		100.0%	1.0%	
LU1-8-1400	HI							70.0	19.0		100.0%	1.0%	
LU1-8-1000	HI	Crestron	Cameo Wireless	CLW-DIMEX-P	120	Forward Phase	Wallbox/System	70.0	19.0		100.0%	1.0%	
LU1-8-1000-WD	WD/WD-2							70.0	19.0		100.0%	1.0%	
LU1-8-1400	HI							70.0	19.0		100.0%	1.0%	
LU1-8-1000	HI	Crestron	Cameo Express Wireless	CLW-DIMSWE-X-E	120	Forward Phase	Wallbox/System	70.0	19.0		100.0%	1.0%	
LU1-8-1000-WD	WD/WD-2							70.0	19.0		100.0%	1.0%	
LU1-8-1400	HI							70.0	19.0		100.0%	1.0%	
LU1-8-1000	HI	Crestron	Cameo Wireless	CLW-DIMSWE-X-P	120	Forward Phase	Wallbox/System	70.0	19.0		100.0%	1.0%	
LU1-8-1000-WD	WD/WD-2							70.0	19.0		100.0%	1.0%	
LU1-8-1400	HI							70.0	19.0		100.0%	1.0%	
LU1-8-1000	HI	Crestron	Cameo Wireless	CLW-DIMUEX-P	120	Forward or Reverse Phase	Wallbox/System	70.0	18.0		100.0%	1.0%	
LU1-8-1000-WD	WD/WD-2							70.0	18.0		100.0%	1.0%	
LU1-8-1400	HI							80.0	27.0		100.0%	1.0%	
LU1-8-1000	HI	Crestron		CLX-1DIMU4	120	Forward or Reverse Phase	Residential/Commercial System	70.0	18.0		100.0%	1.0%	
LU1-8-1000-WD	WD/WD-2							70.0	18.0		100.0%	1.0%	
LU1-8-1400	HI							70.0	18.0		100.0%	1.0%	
LU1-8-1000	HI	Crestron		CLX-2DIMU8	120	Forward or Reverse Phase	Residential/Commercial System	70.0	18.0		100.0%	1.0%	
LU1-8-1000-WD	WD/WD-2							70.0	18.0		100.0%	1.0%	
LU1-8-1400	HI							80.0	28.0		100.0%	1.0%	
LU1-8-1000	HI	Crestron	Wireless Horizon	HZ-DIMEX SERIES	120	Forward Phase	Wallbox/System	75.0	28.0		100.0%	1.0%	
LU1-8-1000-WD	WD/WD-2							80.0	27.0		100.0%	1.0%	
LU1-8-1400	HI							80.0	28.0		100.0%	1.0%	
LU1-8-1000	HI	Crestron	Wireless Horizon	HZ-DIMUEX SERIES	120	Forward or Reverse Phase	Wallbox/System	70.0	18.0		100.0%	1.0%	
LU1-8-1000-WD	WD/WD-2							80.0	27.0		100.0%	1.0%	
LU1-8-1400	HI							70.0	19.0		100.0%	1.0%	
LU1-8-1000	HI	Crestron		P-DIMEX	120	Forward Phase	Wallbox/System	70.0	19.0		100.0%	1.0%	
LU1-8-1000-WD	WD/WD-2							70.0	19.0		100.0%	1.0%	
LU1-8-1400	HI							75.0	20.0		100.0%	1.0%	
LU1-8-1000	HI	Crestron	Zum Wireless	ZUMMESH-DELV	120	Reverse Phase	Wallbox/System	70.0	19.0		100.0%	1.0%	
LU1-8-1000-WD	WD/WD-2							80.0	21.0		100.0%	1.0%	
LU1-8-1400	HI							75.0	24.0		100.0%	1.0%	
LU1-8-1000	HI	Crestron	Zum Wireless	ZUMMESH-DIM	120	Forward Phase	Wallbox/System	73.0	22.0		100.0%	1.0%	
LU1-8-1000-WD	WD/WD-2							75.0	24.0		100.0%	1.0%	
LU1-8-1400	HI							70.0	20.0		100.0%	1.0%	
LU1-8-1000	HI	Crestron	Zum Wireless	ZUMMESH-EXP-16A-DIMU	120	Forward or Reverse Phase	Wallbox/System	70.0	20.0		100.0%	5.0%	
LU1-8-1000-WD	WD/WD-2							70.0	20.0		100.0%	5.0%	
LU1-8-1400	HI							80.0	15.0		100.0%	1.0%	
LU1-8-1000	HI	Vantage		ScenePoint	120	Forward Phase	Residential System	77.0	21.0	10	94.1%	1.6%	
LU1-8-1000-WD	WD/WD-2							74.3	20.5		100	95.2%	2.1%
LU1-8-1400	HI							73.5	17.0		35	95.7%	1.3%
LU1-8-1000	HI	Vantage		SDM12-EM	120	Forward Phase	Residential System	72.0	15.0	10	96.4%	1.4%	
LU1-8-1000-WD	WD/WD-2							69.5	16.0		90	95.1%	1.0%
LU1-8-1400	HI							79.0	18.0		15	95.7%	1.1%
LU1-8-1000	HI	Vantage		UDM-F	120	Forward Phase	Wallbox/System	77.0	18.5	10	94.4%	1.4%	
LU1-8-1000-WD	WD/WD-2							71.5	19.3		90	94.8%	1.2%
LU1-8-1400	HI							76.5	18.0		25	95.4%	1.2%
LU1-8-1000	HI	Vantage		UDS-F	120	Forward Phase	Wallbox/System	78.0	23.0	10	94.4%	1.6%	
LU1-8-1000-WD	WD/WD-2							74.5	22.3		90	95.1%	1.3%
LU1-8-1400	HI							78.0	17.0		10	95.5%	1.0%

Dimmer compatibility testing performed using 120V/60Hz supply.

Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.

The design, specification, or performance of compatible dimmers is subject to change without notice.

For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93001-3 - 01/2023

**DIMMER COMPATIBILITY
800 SERIES**

DRIVER MODELS: DIM2-8-1000/1400/1000-WD, EL1-8-1000/1400/1000-WD, EL1-01-8-1000/1400/1000-WD

LED MODELS: HI, HI-2, WD/WD-2



www.8lighting.com

No.8 Lighting Driver Model	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Recommened Trim Settings		Adjust (Vantage Only)	Dimming Range		
								High-End (%)	Low-End (%)		High-End (%)	Low-End (%)	
DIM2-8													
DIM2-8-1000	HI	Crestron	ilux	CLS-EXP-DIMFLV	120	0-10v	Residential/ Commercial System	75.0	1.0		100.0%	2.0%	
DIM2-8-1000-WD	WD							88.0	9.0		100.0%	2.0%	
DIM2-8-1400	HI							70.0	1.0		100.0%	4.0%	
DIM2-8-1000	HI	Crestron	Cameo	CLW-DIMFLVEX-P	120	0-10v	Wallbox/System	67.0	1.0		100.0%	2.0%	
DIM2-8-1000-WD	WD							80.0	1.0		100.0%	2.0%	
DIM2-8-1400	HI							70.0	1.0		100.0%	13.0%	
DIM2-8-1000	HI	Crestron		CLX-2DIMFLVB	120	0-10v	Residential/ Commercial System	67.0	1.0		100.0%	11.0%	
DIM2-8-1000-WD	WD							90.0	1.0		100.0%	6.0%	
DIM2-8-1400	HI							70.0	1.0		100.0%	4.0%	
DIM2-8-1000	HI	Crestron	Wireless Horizon	HZ-DIMUEX SERIES	120	0-10v	Wallbox/System	67.0	1.0		100.0%	5.0%	
DIM2-8-1000-WD	WD							85.0	1.0		100.0%	3.0%	
DIM2-8-1400	HI							80.0	1.0		100.0%	8.0%	
DIM2-8-1000	HI	Crestron	Zum Wireless	ZUMMESH-5A-LV	120	0-10v	Wallbox/System	67.0	1.0		100.0%	8.0%	
DIM2-8-1000-WD	WD							85.0	1.0		100.0%	5.0%	
DIM2-8-1400	HI							70.0	1.0		100.0%	12.0%	
DIM2-8-1000	HI	Crestron	Zum Wireless	ZUMMESH-JBOX	120	0-10v	Wallbox/System	67.0	1.0		100.0%	8.0%	
DIM2-8-1000-WD	WD							85.0	1.0		100.0%	6.0%	
DIM2-8-1400	HI							70.0	1.0		100.0%	12.0%	
DIM2-8-1000	HI-2	Lutron	Diva	DVST-XX	120	0-10v	Wallbox	High & Low-End Trim Required			100.0%	10.3%	
DIM2-8-1000	HI							100.0%	6.7%				
DIM2-8-1000-WD	WD/WD-2							100.0%	3.6%				
DIM2-8-1400	HI	Lutron	Homeworks QSX	LQSE-4T5-120-D	120	0-10v	Residential/ Commercial System	85.0	2.0		100.0%	7.8%	
DIM2-8-1000	HI-2							85.0	1.0		100.0%	6.1%	
DIM2-8-1000-WD	WD/WD-2							90.0	1.0		100.0%	3.6%	
DIM2-8-1400	HI	Lutron	Nova T	NTSTV-DV-XX	120	0-10v	Wallbox	High & Low-End Trim Required			100.0%	6.4%	
DIM2-8-1000	HI-2							100.0%	9.1%				
DIM2-8-1000	HI							100.0%	7.5%				
DIM2-8-1000-WD	WD/WD-2	Vantage		LVOS-0-10-PWM	120	0-10v	Residential/ Commercial System	5 (VDC)	0.5 (VDC)	100	95.1%	5.9%	
DIM2-8-1400	HI							7.28 (VDC)	0.39 (VDC)		100	94.9%	2.0%
DIM2-8-1000-WD	WD/WD-2							5.4 (VDC)	0.6 (VDC)		100	94.9%	5.0%
DIM2-4-1400	HI												
EL1-8													
EL1-8-1000	HI-2	Lutron	Diva	DVST-XX	120	0-10v	Wallbox	High & Low-End Trim Required			100.0%	2.3%	
EL1-8-1000	HI							100.0%	2.0%				
EL1-8-1000-WD	WD/WD-2							100.0%	0.9%				
EL1-8-1400	HI	Lutron	Homeworks QSX	LQSE-4T5-120-D	120	0-10v	Residential/ Commercial System	90.0	3.0		100.0%	2.3%	
EL1-8-1000	HI-2							90.0	2.0		100.0%	2.0%	
EL1-8-1000-WD	WD/WD-2							90.0	3.0		100.0%	0.9%	
EL1-8-1400	HI	Lutron	Nova T	NTSTV-DV-XX	120	0-10v	Wallbox	High & Low-End Trim Required			100.0%	2.2%	
EL1-8-1000	HI-2							100.0%	2.3%				
EL1-8-1000	HI							100.0%	2.0%				
EL1-8-1000-WD	WD/WD-2	Vantage		LVOS-0-10-PWM	120	0-10v	Residential/ Commercial System	7.8 (VDC)	1.4 (VDC)	100	95.0%	2.1%	
EL1-8-1400	HI							8.1 (VDC)	1.5 (VDC)		100	95.2%	2.1%
EL1-8-1000-WD	WD/WD-2							7.8 (VDC)	1.5 (VDC)		100	94.7%	3.7%
EL1-8-1400	HI												
EL1-01-8													
EL1-01-8-1000	HI	Crestron	ilux	CLS-EXP-DIMFLV	120	0-10v	Residential/ Commercial System	90.0	20.0		100.0%	1.0%	
EL1-01-8-1000	HI	Crestron	Cameo	CLW-DIMFLVEX-P	120	0-10v	Wallbox/System	90.0	9.0		100.0%	1.0%	
EL1-01-8-1000	HI	Crestron		CLX-2DIMFLVB	120	0-10v	Residential/ Commercial System	90.0	6.0		100.0%	2.0%	
EL1-01-8-1000	HI	Crestron	Wireless Horizon	HZ-DIMUEX SERIES	120	0-10v	Wallbox/System	90.0	9.0		100.0%	3.0%	
EL1-01-8-1000	HI	Crestron	Zum Wireless	ZUMMESH-5A-LV	120	0-10v	Wallbox/System	90.0	7.0		100.0%	1.0%	
EL1-01-8-1000	HI	Crestron	Zum Wireless	ZUMMESH-JBOX	120	0-10v	Wallbox/System	90.0	7.0		100.0%	2.0%	
EL1-01-8-1000	HI	Crestron	Zum Wireless	ZUMNETLINK-JBOX	120	0-10v	Wallbox/System	90.0	7.0		100.0%	1.0%	

No.8 Lighting Driver Model	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Recommended Trim Settings		Adjust (Vantage Only)	Dimming Range		
								High-End (%)	Low-End (%)		High-End (%)	Low-End (%)	
EL1-01-8 (Continued)													
EL1-01-8-1000	HI-2	Lutron	Diva	DVST-XX	120	0-10v	Wallbox	High & Low-End Trim Required			100.0%	0.1%	
EL1-01-8-1000	HI										100.0%	0.1%	
EL1-01-8-1000-WD	WD/WD-2										100.0%	0.0%	
EL1-01-8-1400	HI	Lutron	Homeworks QSX	LQSE-4TS-120-D	120	0-10v	Residential/ Commercial System	90.0	3.0		100.0%	0.1%	
EL1-01-8-1000	HI-2							90.0	3.0		100.0%	0.2%	
EL1-01-8-1000	HI							90.0	18.0		100.0%	1.5%	
EL1-01-8-1000-WD	WD/WD-2							90.0	3.0		100.0%	0.1%	
EL1-01-8-1400	HI										100.0%	0.1%	
EL1-01-8-1000	HI-2	Lutron	Nova T	NTSTV-DV-XX	120	0-10v	Wallbox	High & Low-End Trim Required			100.0%	0.1%	
EL1-01-8-1000	HI										100.0%	0.1%	
EL1-01-8-1000-WD	WD/WD-2										100.0%	0.9%	
EL1-01-8-1400	HI										100.0%	0.1%	
EL1-01-8-1000	HI	Vantage		LVOS-0-10-PWM	120	0-10v	Residential/ Commercial System	7.85 (VDC)	1.5 (VDC)	100	94.9%	1.2%	
EL1-01-8-1000	HI							8.0 (VDC)	1.6 (VDC)		100	95.0%	3.0%
EL1-01-8-1000-WD	WD/WD-2							7.8 (VDC)	1.5 (VDC)		100	95.1%	0.5%
EL1-01-8-1400	HI												

Dimmer compatibility testing performed using 120V/60Hz supply.

Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.

The design, specification, or performance of compatible dimmers is subject to change without notice.

For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93001-4 - 01/2023

DIMMER COMPATIBILITY

800 SERIES

DRIVER MODELS: EL2-8-1000/1400/1000-WD, EL2-01-8-1000/1400/1000-WD

LED MODELS: HI, HI-2, WD/WD-2



www.8lighting.com

No.8 Lighting Driver Model	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Recommended Trim Settings		Dimming Range	
								High-End (%)	Low-End (%)	High-End (%)	Low-End (%)
EL2-8											
EL2-8-1000	HI-2	Lutron	Homeworks QSX	LQSE-2DAL-D	120	DALI	Residential/ Commercial System	100.0	1.0	100.0%	1.4%
EL2-8-1000	HI							100.0	1.0	100.0%	1.3%
EL2-8-1000-WD	WD/WD-2							100.0	1.0	100.0%	0.6%
EL2-8-1400	HI	Vantage		DMX-DALI-GW	120	DALI	Residential/ Commercial System	100.0	1.0	100.0%	1.4%
EL2-8-1000	HI-2							100.0	1.0	100.0%	1.4%
EL2-8-1000	HI							100.0	1.0	100.0%	1.3%
EL2-8-1000-WD	WD/WD-2							100.0	1.0	100.0%	0.6%
EL2-8-1400	HI							100.0	1.0	100.0%	1.4%
EL2-01-8											
EL2-01-8-1000	HI-2	Lutron	Homeworks QSX	LQSE-2DAL-D	120	DALI	Residential/ Commercial System	100.0	1.0	100.0%	0.5%
EL2-01-8-1000	HI							100.0	1.0	100.0%	0.4%
EL2-01-8-1000-WD	WD/WD-2							100.0	1.0	100.0%	0.0%
EL2-01-8-1400	HI	Vantage		DMX-DALI-GW	120	DALI	Residential/ Commercial System	100.0	1.0	100.0%	0.5%
EL2-01-8-1000	HI-2							100.0	1.0	100.0%	0.5%
EL2-01-8-1000	HI							100.0	1.0	100.0%	0.4%
EL2-01-8-1000-WD	WD/WD-2							100.0	1.0	100.0%	0.0%
EL2-01-8-1400	HI							100.0	1.0	100.0%	0.5%

Dimmer compatibility testing performed using 120V/60Hz supply.

Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.

The design, specification, or performance of compatible dimmers is subject to change without notice.

For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93001-5 - 01/2023

DIMMER COMPATIBILITY

800 SERIES

DRIVER MODELS: EL3-8-1000-TW, EL4-8-1000-TW, EL5-8-1000-TW

LED MODEL: TW



www.8lighting.com

No.8 Lighting Driver Model	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Recommended Trim Settings		Dimming Range	
								High-End (%)	Low-End (%)	High-End (%)	Low-End (%)
EL3-8-1000-TW											
EL3-8-1000-TW	TW	Lutron	Homeworks QSX	LQSE-2DAL-D	120	DALI	Residential/ Commercial System	100.0	1.0	100.0%	0.0%
EL3-8-1000-TW	TW	Vantage		DMX-DALI-GW	120	DALI	Residential/ Commercial System	100.0	1.0	100.0%	0.0%
EL4-8-1000-TW											
EL4-8-1000-TW	TW	Lutron	Homeworks QSX	LQSE-2DAL-D	120	DMX	Residential/ Commercial System	100.0	1.0	99.8%	0.3%
EL4-8-1000-TW	TW	Vantage		DMX-DALI-GW	120	DMX	Residential/ Commercial System	100.0	1.0	99.8%	0.3%
EL5-8-1000-TW											
EL5-8-1000-TW	TW	Lutron	Divia	DVST-XX	120	0-10v	Wallbox	High & Low-End Trim		100.0%	0.1%
EL5-8-1000-TW	TW	Lutron	Homeworks QSX	LQSE-4T5-120-D	120	0-10v	Residential/ Commercial System	90.0	10.0	100.0%	0.1%
EL5-8-1000-TW	TW	Lutron	Nova T	NTSTV-DV-XX	120	0-10v	Wallbox	High & Low-End Trim		100.0%	0.1%
EL5-8-1000-TW	TW	Vantage		LVOS-0-10-PWM	120	0-10v	Residential/ Commercial System	8.8 (VDC)	1.4 (VDC)	100.0%	0.1%

Dimmer compatibility testing performed using 120V/60Hz supply.

Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.

The design, specification, or performance of compatible dimmers is subject to change without notice.

For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93001-6 - 01/2023