

400 Series – Recessed LED

REMODEL



400-R – ADJUSTABLE LED

- Type IC Rated / Airtight
- Fully adjustable (0-35° vertical / 360° horizontal) for general, accent, and wall wash lighting applications
- Accommodates ceiling thicknesses ranging from 1/2" – 5-1/2" without affecting aiming or adjustment
- Six LED options: **HI** or **HI-2** 2700K or 3000K 94 CRI Static White, and **WD** 3000-1800K or **WD-2** 2800-2200K 97 CRI Warm Dim
- Four beam spread options: 10°, 15°, 25°, and 40°
- Five beam enhancing and three color filtering lens options
- Seven Integral and Six Remote dimming driver options
- Six Round or Square 2" aperture FLAT and BEVEL trim options
- Two trim mounting options: Flanged (for multiple ceiling types) and Flangeless for sheetrock
- Two trim finish options
- Three trim lens options rated for use in DRY, DAMP, or WET locations and residential steam applications
- 2022 CA JAB Compliant

400-R SERIES PERFORMANCE SUMMARY

LED:	HI	HI-2	WD	WD-2
Correlated Color Temperature:	2700K/3000K	2700K/3000K	3000K-1800K	2800K-2200K
Color Rendering Index:	94	94	97	97
Delivered Lumens:	964-1037	1006-1082	818	809
Wattage:	14	14.5	15	15
Delivered Lumens Per Watt:	69-74	69-75	56	55

Performance shown for FS-4 trim.
 HI and HI-2 LED data shown for 2700-3000K.
 WD and WD-2 Warm Dimming LED data shown for 3000K and 2800K.



526 Portal Street
 Cotati, CA 94931
 USA
 P 707.794.0888
 www.8lighting.com

All No. 8 Lighting fixtures and components are UL Listed to both U.S. and Canadian requirements. No. 8 Lighting trims and lamp modules are protected by one or more U.S. Patents. No. 8 Lighting reserves the right to change details of design, materials, and finish.

© 2023 No. 8 Lighting



09/2023

93102-05