

MPT2 – LED Monopoint Gen 2

FEATURES

- **MPT2-4** 2-1/2" diameter with 4" Round or Square canopy for INTEGRAL driver
- **MPT2-RT-2/4** 2-1/2" diameter with 2-1/2" or 4" Round or Square canopy for REMOTE drivers
- Rotates 320° and tilts 110°
- Surface mount for Ceiling or Wall applications
- Four stem length options
- Six LED options: **HI** or **HI-2** 2700K or 3000K 94 CRI Static White, and **WD** 3000-1800K or **WD-2** 2800-2200K 97 CRI Warm Dim
- Four beam spread options: 10°, 15°, 25°, and 40°
- Five beam enhancing and three color filtering lens options
- One Integral and six Remote dimming driver options
- Remote driver can be located up to 100' from fixture
- Four finish options
- 2022 CA JA8 Compliant

MPT2-4R/S – INTEGRAL DRIVER and 4" CANOPY



MPT2-4R

MPT2-4S

MPT2-RT-4R/S – REMOTE DRIVER and 4" CANOPY



MPT2-RT-4R

MPT2-RT-4S

MPT2-RT-2R/S – REMOTE DRIVER and 2-1/2" CANOPY



MPT2-RT-2R


MPT2-RT-2S

MPT2 PERFORMANCE SUMMARY

LED:	HI	HI-2	WD	WD-2
Correlated Color Temperature:	2700/3000K	2700/3000K	3000K-1800K	2800K-2200K
Color Rendering Index:	94	94	97	97
Delivered Lumens:	1016-1426	1037-1115	927	904
Wattage:	14/20	14.5	15	15
Delivered Lumens Per Watt:	67-78	72-77	63	62

HI and HI-2 LED data shown for 2700-3000K.

WD and WD-2 Warm Dimming LED data shown for 3000K and 2800K.



WHITE



SATIN ALUMINUM



OIL-RUBBED BRONZE



BLACK



526 Portal Street
Cotati, CA 94931
USA
P 707.794.0888
www.8lighting.com

All No. 8 Lighting fixtures and components are UL Listed to both U.S. and Canadian requirements. No. 8 Lighting trims and lamp modules are protected by one or more U.S. Patents. No. 8 Lighting reserves the right to change details of design, materials, and finish.

© 2023 No. 8 Lighting



09/2023

93351-05