

200 Series – Recessed LED

REMODEL

FEATURES

- Two light engine options for ROUND or SQUARE trims: **202-RM** Adjustable (0-30°vertical/ 360°horizontal) and **203-RM** Wall Wash deliver up to 1232 lumens at 14 watts
- Four 92 CRI White LED options: 2700K, 3000K, 3500K, and 4000K
- Two 97 and 95 CRI Warm Dim LED options: 3000-1800K and 2800-2200K
- Four beam spread options: 15°, 25°, 40°, and 60°
- Five beam enhancing lens options
- Nine Integral and Six Remote dimming driver options
- Six Round or Square trim options: 1-7/8" aperture FLAT, 2-1/4" aperture BEVEL, and 2-3/4" angle-cut aperture WALL WASH
- Two trim mounting options: Flanged (for multiple ceiling types) and Flange-less for sheetrock
- Four trim finish options and three trim lens options rated for use in DRY, DAMP, or WET locations and residential steam applications
- Type Non-IC / Airtight

202-RM/203-RM – ADJUSTABLE/WALL WASH LED



202-RM ADJUSTABLE and 203-RM WALL WASH PERFORMANCE SUMMARY

| Model: | 202-RM-HI | 202-RM-WD | 202-RM-WD-2 | 203-RM-HI | 203-RM-WD | 203-RM-WD-2 |
|----------------------------|-----------|-----------|-------------|-----------|-----------|-------------|
| Delivered Lumens: | 785-1232 | 523-760 | 507-737 | 939-1059 | 714-727 | 693-705 |
| Delivered Lumens Per Watt: | 56-88 | 35-51 | 34-49 | 67-76 | 48 | 47 |

Performance range shown for Model 202-RM with Square and Round FLAT and BEVEL trims, HI Static White LED at 2700-4000K, WD Warm Dim LED at 3000K, and WD-2 LED at 2800K.
Performance range shown for Model 203-RM with Square and Round WALL WASH trims, HI Static White LED at 2700-4000K, WD Warm Dim LED at 3000K, and WD-2 LED at 2800K.



526 Portal Street
Cotati, CA 94931
USA
P 707.794.0888
www.8lighting.com

All No. 8 Lighting fixtures and components are UL listed to both U.S. and Canadian requirements. No. 8 Lighting trims and lamp modules are protected by one or more U.S. Patents. No. 8 Lighting reserves the right to change details of design, materials, and finish.

© 2024 No. 8 Lighting



03/2024

93002-06