


# 804D – Deep Ceiling Recessed LED

## FEATURES

- 4" overall height
- Designed for use with 30mm BASWA Acoustic Plaster Ceiling Systems
- Accommodates ceiling thicknesses of 1-1/8" to 1-1/2" with minimal cut-off
- IC / Airtight / Chicago Plenum rated
- Tested and rated for direct contact with closed-cell spray-foam insulation
- Accepts **J2S** 0-45° adjustable accent and wall wash, **K2S** fixed position, or **M2S** 35-90° adjustable mirror reflector lamp modules
- Seven LED options: **HI** or **HI-2** 2700K or 3000K 94 CRI Static White, **WD** 3000-1800K or **WD-2** 2800-2200K 97 CRI Warm Dim, and **TW** 4700-2200K 95 CRI Tunable White
- Four beam spread options: 10°, 15°, 25°, and 40°
- Five beam enhancing and three color filtering lens options
- Multiple Integral dimming driver options including: <1% Forward/Reverse Phase, 0.1/1% 0-10V, 0.1/1% DALI, 0.1% DMX, and 0.1%/1% Lutron EcoSystem
- Accepts **800 P-Series** trim models: **FS-P**, **FR-P**, **FS-LG-P**, and **FR-LG-P**



**804D-S/R** – RECESSED LED HOUSING



**J2S** – LED ADJUSTABLE



**K2S** – LED FIXED POSITION



**M2S** – LED MIRROR REFLECTOR

## 804D PERFORMANCE SUMMARY

LED:	HI	HI-2	WD	WD-2	TW
Correlated Color Temperature:	2700K/3000K	2700K/3000K	3000-1800K	2800-2200K	4700-2200K
Color Rendering Index:	94	94	97	97	95
Delivered Lumens:	968-1472	971-1129	837-923	834-915	1018
Wattage:	14/20	14.5	14.5	14.5	14
Delivered Lumens Per Watt:	63-80	67-78	58-64	58-63	73

Performance summary for J2S and K2S Lamp Modules with FS-LG-P/NL trim.  
 HI and HI-2 LED data shown for 2700-3000K.  
 WD and WD-2 Warm Dimming LED data shown for 3000K and 2800K.  
 TW Tunable White LED data shown for 3000K. TW LED option available with J2S Lamp Module only.



526 Portal Street  
 Cotati, CA 94931  
 USA  
 P 707.794.0888  
 www.8lighting.com


All No. 8 Lighting fixtures and components are UL listed to both U.S. and Canadian requirements. No. 8 Lighting trims and lamp modules are protected by one or more U.S. Patents. No. 8 Lighting reserves the right to change details of design, materials, and finish.  
 © 2024 No. 8 Lighting




# 800 Series – Trim Packages

## FEATURES


- Round and Square
- Flangeless
- Minimal 1-3/4" and 2-3/4" apertures
- UL WET LISTED and IP54 Rated for use in DRY, DAMP, or WET locations (covered ceiling applications only)
- Approved for use in residential steam applications. Not for use in commercial steam applications.
- Compatible with all Number Eight Lighting **800 Series** housings
- Available in five designer finishes:



WHITE



POLISHED NICKEL



SATIN NICKEL




OIL-RUBBED BRONZE




BLACK

## P-Series – Plaster/Sheetrock Ceiling Applications



FS-P



FR-P



FS-LG-P



FR-LG-P



526 Portal Street  
Cotati, CA 94931  
USA  
P 707.794.0888  
www.8lighting.com

All No. 8 Lighting fixtures and components are UL Listed to both U.S. and Canadian requirements. No. 8 Lighting trims and lamp modules are protected by one or more U.S. Patents. No. 8 Lighting reserves the right to change details of design, materials, and finish.

© 2024 No. 8 Lighting

