




# MPT2 – LED Monopoint Gen 2


## FEATURES

- **MPT2-4**  
4" Canopy for INTEGRAL Driver
- **MPT2-RT-2/4**  
2.5" or 4" Canopy for REMOTE Driver
- **Mounting Options** (Wall or Ceiling)  
Surface Mount: 2.5" or 4" Round or Square Canopy
- **0-110° Adjustable**
- **Stem Options**  
6, 12, 18, or 24
- **LED Options**  
Static White  
Warm Dimming
- **Optic Options**  
10°, 15°, 25°, and 40°
- **Optical Accessories**  
Five beam enhancing lens options  
Three color filtering lens options
- **Driver Options**  
INTEGRAL: Forward/Reverse Phase  
REMOTE: 0-10V, DALI, EcoSystem
- **Four Finish Options**

  
WHITE

  
SATIN ALUMINUM

  
OIL-RUBBED BRONZE

  
BLACK
- **CA JA8 2025 Compliant**

## MPT2-4R/S – INTEGRAL DRIVER and 4" CANOPY



MPT2-4R



MPT2-4S

## MPT2-RT-4R/S – REMOTE DRIVER and 4" CANOPY



MPT2-RT-4R



MPT2-RT-4S

## MPT2-RT-2R/S – REMOTE DRIVER and 2-1/2" CANOPY



MPT2-RT-2R



MPT2-RT-2S

## MPT2 SERIES PERFORMANCE SUMMARY

	Static White			Warm Dimming		
LED Options	HI	HI-2	HI-3	WD	WD-2	WD-4
Delivered Lumens	1092/1426	1015	1036	927	904	916
CRI	94	94	97	97	97	97
R9	59	63	99	81	78	74
Efficacy	73/78	77	70	63	62	63
CCT Options	2700K, 3000K			3000K-1800K	2800K-2200K	3000K-2200K

Static White LED data shown for 3000K.

Warm Dimming LED data shown for 3000K and 2800K.



526 Portal Street  
Cotati, CA 94931  
USA  
P 707.794.0888  
www.8lighting.com

All No. 8 Lighting fixtures and components are UL Listed to both U.S. and Canadian requirements. No. 8 Lighting trims and lamp modules are protected by one or more U.S. Patents. No. 8 Lighting reserves the right to change details of design, materials, and finish.

© 2025 No. 8 Lighting



04/2025

93351-06