

Photometric / Colorimetric / Electric Report

Fixture Model:


200-HD-IC-S-HI3500-60-EL1-2-500-FLS-2-30d

Trim Model:

FLS-2-WH

Date:

8/11/2022



Light efficiency:

35 Lumen/Watt

Light quality:

CRI: 94.9

Color temperature:

3475 K

CIE 1931:

x: 0.405
y: 0.387


Output: 673 lm

Peak: 1658 cd



Power: 19.5 W

PF: 0.98


Spectra:




Color Details



TM-30: 91.3



CRI: 94.9 (R1-R8)



CRI R Values:

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
96.0	98.4	98.2	94.4	94.8	95.7	93.7	87.7	72.3	94.3	95.0	77.0	97.1	98.5	93.4


TM30 C Values:

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
91.3	93.9	93.3	93.5	92.4	96.8	92.8	94.5	90.6	85.7	86.7	90.7	93.4	89.5	89.3	88.3

CQS Q values:

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
91.4	97.7	89.3	87.4	90.9	93.6	94.9	95.3	99.1	96.2	95.2	95.0	95.2	91.8	91.9

CQS: 93.0



Color Parameters:

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3475 K	94.9	72.3	91.3	98.3	93.0	0.405	0.387	0.237	0.340	-0.0015

TM-30 Details







Rf 91.3

Fidelity index Rf

Rg 98.3

Gamut index Rg

Hue Bin	R _f	Shifts (%)	
		Chroma	Hue
1	91	-4%	1%
2	94	-2%	2%
3	93	-1%	3%
4	94	-2%	0%
5	92	-5%	0%
6	97	0%	0%
7	93	-4%	2%
8	94	-2%	3%
9	91	-2%	6%
10	86	0%	10%
11	87	4%	8%
12	91	5%	1%
13	93	2%	-4%
14	90	4%	-7%
15	89	-1%	-6%
16	88	-1%	-6%



Aiming Angle

