

## Photometric / Colorimetric / Electric Report

Fixture Model:

200-HD-WD-R-WD-15-NFL-DIM1-2-350-FLR-2

Trim Model:

FLR-2-WH

Date:

2/24/2022



Light efficiency:

35 Lumen/Watt

Light quality:

CRI: 96.8

Color temperature:

3124 K

CIE 1931:

x: 0.427  
y: 0.398


Output: 511 lm

Peak: 2245 cd



Power: 14.6 W

PF: 0.99


Spectra:




## Color Details



TM-30: 93.4



CRI: 96.8 (R1-R8)



CRI R Values:

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
98.4	98.7	96.9	98.2	97.7	96.8	96.0	91.9	80.9	95.3	97.3	81.6	99.0	97.3	96.0


TM30 C Values:

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
94.6	96.0	94.4	95.5	93.4	96.5	93.8	98.4	94.4	89.8	89.3	91.1	94.1	90.9	91.8	88.4

CQS Q values:

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
92.8	96.9	89.7	90.3	94.2	95.9	93.2	95.1	97.5	95.4	95.8	96.2	96.3	93.2	93.1

CQS: 93.8



Color Parameters:

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3124 K	96.8	80.9	93.4	100.7	93.8	0.427	0.398	0.247	0.345	-0.0012

# TM-30 Details







**Rf 93.4**

Fidelity index Rf


**Rg 100.7**

Gamut index Rg

Hue Bin	R <sub>f</sub>	Shifts (%)	
		Chroma	Hue
1	95	-2%	0%
2	96	-1%	1%
3	94	0%	2%
4	96	-1%	0%
5	93	-3%	2%
6	96	1%	1%
7	94	-2%	1%
8	98	0%	0%
9	94	-1%	4%
10	90	0%	6%
11	89	2%	7%
12	91	6%	1%
13	94	2%	-3%
14	91	4%	-6%
15	92	0%	-4%
16	88	1%	-9%



## Beam Details



### Beam Intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
2245lx	561lx	249lx	140lx	90lx	62lx	46lx	35lx	28lx	22lx	19lx	16lx	13lx	11lx	10lx	9lx	8lx	7lx	6lx	6lx
208.6fc	52.2fc	23.2fc	13fc	8.3fc	5.8fc	4.3fc	3.3fc	2.6fc	2.1fc	1.7fc	1.4fc	1.2fc	1.1fc	0.9fc	0.8fc	0.7fc	0.6fc	0.6fc	0.5fc

### Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2245	2185	2025	1830	1622	1410	1198	980	779	598	448	325	225	146	89	53	31	18	11	8
100%	97%	90%	81%	72%	63%	53%	44%	35%	27%	20%	14%	10%	7%	4%	2%	1%	1%	1%	0%

### Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2245	2185	2025	1830	1622	1410	1198	980	779	598	448	325	225	146	89	53	31	18	11	8
100%	97%	90%	81%	72%	63%	53%	44%	35%	27%	20%	14%	10%	7%	4%	2%	1%	1%	1%	0%

### Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2245	2185	2025	1830	1622	1410	1198	980	779	598	448	325	225	146	89	53	31	18	11	8
100%	97%	90%	81%	72%	63%	53%	44%	35%	27%	20%	14%	10%	7%	4%	2%	1%	1%	1%	0%

### Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2245	2185	2025	1830	1622	1410	1198	980	779	598	448	325	225	146	89	53	31	18	11	8
100%	97%	90%	81%	72%	63%	53%	44%	35%	27%	20%	14%	10%	7%	4%	2%	1%	1%	1%	0%

Beam angle 50%	Field angle 10%	Cut-off angle 2.5%	Intensity ratio in 120°	Intensity ratio in 90°
25.4°	48°	59.5°	99.5%	99.4%