

Photometric / Colorimetric / Electric Report

Fixture Model:


804S-J2S-WD-25-DIM1-8-350-FS-LG-P-1-WH-NL

Trim Model:

FS-LG-P-1-WH-NL

Date:

4/8/2022



Light efficiency:

50 Lumen/Watt

Light quality:

CRI: 97.0

Color temperature:

3118 K

CIE 1931:

**x: 0.426
y: 0.394**


Output: 727 lm

Peak: 2136 cd



Power: 14.5 W

PF: 0.99


Spectra:




Color Details



TM-30: 93.3



CRI: 97.0 (R1-R8)



CRI R Values:

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
98.9	99.2	98.0	98.3	98.2	96.4	95.3	91.9	82.3	97.6	97.5	82.7	99.6	98.0	96.9


TM30 C Values:

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
94.4	95.9	94.6	95.3	93.4	96.6	93.4	98.3	93.7	89.5	89.6	91.1	93.7	90.9	91.6	88.7

CQS Q values:

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
92.7	96.7	90.0	90.0	93.8	96.4	93.2	94.7	97.8	95.5	95.5	95.6	95.6	93.3	93.1

CQS: 93.7



Color Parameters:

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3118 K	97.0	82.3	93.3	100.6	93.7	0.426	0.394	0.248	0.344	-0.0024

TM-30 Details







Rf 93.3

Fidelity index Rf


Rg 100.6

Gamut index Rg

Hue Bin	R _f	Shifts (%)	
		Chroma	Hue
1	94	-2%	1%
2	96	-1%	1%
3	95	0%	2%
4	95	-2%	0%
5	93	-3%	1%
6	97	1%	1%
7	93	-2%	1%
8	98	0%	0%
9	94	0%	4%
10	89	0%	6%
11	90	3%	7%
12	91	6%	0%
13	94	2%	-4%
14	91	4%	-6%
15	92	0%	-4%
16	89	1%	-9%



Beam Details



Beam Intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
2136lx	534lx	237lx	133lx	85lx	59lx	44lx	33lx	26lx	21lx	18lx	15lx	13lx	11lx	9lx	8lx	7lx	7lx	6lx	5lx
198.4fc	49.6fc	22fc	12.4fc	7.9fc	5.5fc	4fc	3.1fc	2.4fc	2fc	1.6fc	1.4fc	1.2fc	1fc	0.9fc	0.8fc	0.7fc	0.6fc	0.5fc	0.5fc

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2136	2107	2023	1893	1733	1552	1360	1165	973	797	641	506	399	315	250	200	161	129	101	76
100%	99%	95%	89%	81%	73%	64%	55%	46%	37%	30%	24%	19%	15%	12%	9%	8%	6%	5%	4%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2136	2107	2023	1893	1733	1552	1360	1165	973	797	641	506	399	315	250	200	161	129	101	76
100%	99%	95%	89%	81%	73%	64%	55%	46%	37%	30%	24%	19%	15%	12%	9%	8%	6%	5%	4%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2136	2107	2023	1893	1733	1552	1360	1165	973	797	641	506	399	315	250	200	161	129	101	76
100%	99%	95%	89%	81%	73%	64%	55%	46%	37%	30%	24%	19%	15%	12%	9%	8%	6%	5%	4%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2136	2107	2023	1893	1733	1552	1360	1165	973	797	641	506	399	315	250	200	161	129	101	76
100%	99%	95%	89%	81%	73%	64%	55%	46%	37%	30%	24%	19%	15%	12%	9%	8%	6%	5%	4%

Beam angle 50%	Field angle 10%	Cut-off angle 2.5%	Intensity ratio in 120°	Intensity ratio in 90°
30°	58.8°	80.1°	99.5%	98.7%