

No. 8 Lighting LED Product Comparison Guide

	800 SERIES	400 SERIES	200 SERIES	MPT3 SERIES
MOUNTING TYPE	RECESSED	RECESSED	RECESSED	SURFACE MOUNTED
APPLICATION	NEW CONSTRUCTION	NEW CONSTRUCTION or REMODEL	NEW CONSTRUCTION or REMODEL	NEW CONSTRUCTION or REMODEL
HOUSING/ CONFIGURATION OPTIONS	<ul style="list-style-type: none"> 2-1/8" H Single and Multi-Lamp 4" H Single and Multi-Lamp Rated for Direct Contact with Standard and Spray Foam Insulation Air-Tight Chicago Plenum (CCEA) Rated 	<ul style="list-style-type: none"> 4-7/8" H Single Lamp 5-3/8" H Single Lamp Plenum Rated IC-Rated for Standard and Spray Foam Insulation* Air-Tight Chicago Plenum (CCEA) Rated* <p><small>*Requires CP-Rated Housing for Spray Foam and Plenum Rated Applications</small></p>	<ul style="list-style-type: none"> 4-1/4" H Single Lamp (202 and 203) 5" H Single Lamp (200HD) 5-3/8" H Single Lamp IC-CP Rated (202, 203, and 200-HD) IC-Rated for Standard and Spray Foam Insulation* Air-Tight ** Chicago Plenum (CCEA) Rated* <p><small>*Requires IC-CP Rated Housing for IC and Plenum Rated Applications</small></p> <p><small>**Requires IC-CP Rated Housing for Airtight Applications with 200-HD Models</small></p>	<ul style="list-style-type: none"> 2-1/2" Square and Round Housing Options with 1-3/4" Aperture 2-1/2" and 4" Square and Round Canopy Options Ceiling or Wall Mount Four Stem Length Options
2025 CA JAB COMPLIANT	✓	✓	w/ IC-CP Housing Option	✓
LED OPTIONS	<ul style="list-style-type: none"> Static White: 2700K and 3000K Warm Dimming: 3000-1800K, 2800-2200K, and 3000-2200K Tunable White: 4700-2200K 	<ul style="list-style-type: none"> Static White: 2700K and 3000K Warm Dimming: 3000-1800K, 2800-2200K, and 3000-2200K 	<ul style="list-style-type: none"> Static White: 2700K and 3000K Warm Dimming: 3000-1800K, 2800-2200K, and 3000-2200K 	<ul style="list-style-type: none"> Static White: 2700K and 3000K Warm Dimming: 3000-1800K, 2800-2200K, and 3000-2200K Tunable White: 4700-2200K
DELIVERED LUMENS @ 3000K CCT	<ul style="list-style-type: none"> Static White: 1044-4176 lumens Warm Dimming: 922-3348 lumens Tunable White: 1018-4072 lumens 	<ul style="list-style-type: none"> Static White: 1082 lumens Warm Dimming: 818 lumens 	<ul style="list-style-type: none"> Static White: 1151-2026 lumens Warm Dimming: 760 lumens 	<ul style="list-style-type: none"> Static White: 998-1489 lumens Warm Dimming: 1057 lumens Tunable White: 1087 lumens
LAMP MODULE OPTIONS	<ul style="list-style-type: none"> Adjustable Accent/Wall Wash (0°- 45°) Adjustable Accent/Wall Wash (0°- 35°) Fixed Downlight Fixed Wall Wash Adjustable Mirror Reflector (35°-90°) 	<ul style="list-style-type: none"> Adjustable Accent/Wall Wash (0°- 35°) 	<ul style="list-style-type: none"> Adjustable Accent/Wall Wash (0°-30°) Fixed Wall Wash 	<ul style="list-style-type: none"> Position 1: Adjustable (0°- 110°) Wall or Ceiling Mount Position 2: Adjustable (0°- 50°) Wall or Ceiling Mount Position 3: Fixed (0°) Ceiling Mount <p><small>Note: Positions 1-3 can be set before or after installation.</small></p>
OPTIC OPTIONS	<ul style="list-style-type: none"> 10°, 15°, 25°, and 40° Beam enhancing lenses: Narrow, Medium, Wide, Extra Wide, and Linear Spread Color filtering lenses: 2400K, 2700K, and 3500K 	<ul style="list-style-type: none"> 10°, 15°, 25°, and 40° Beam enhancing lenses: Narrow, Medium, Wide, Extra Wide, and Linear Spread Color filtering lenses: 2400K, 2700K, and 3500K 	<ul style="list-style-type: none"> 15°, 25°, 40°, and 60° Beam enhancing lenses: Narrow, Medium, Wide, Extra Wide, and Linear Spread 	<ul style="list-style-type: none"> 10°, 15°, 25°, and 40° Beam enhancing lenses: Narrow, Medium, Wide, Extra Wide, Linear Spread, and HEX Louver Color filtering lenses: 2400K, 2700K, and 3500K
DRIVER OPTIONS	<ul style="list-style-type: none"> <1% Forward/Reverse Phase 0.1% 0-10v 1% 0-10v 0.1% DALI 1% DALI 0.1% DALI 2-Channel* 0.1% DMX 2-Channel* 0.1% 0-10v 2-Channel* 0.1% EcoSystem 1% EcoSystem <p><small>*Available with Tunable White LED option</small></p>	<ul style="list-style-type: none"> <1% Forward/Reverse Phase 0.1% 0-10v 1% 0-10v 0.1% DALI 1% DALI 1% Forward Phase 0.1% EcoSystem 1% EcoSystem 	<ul style="list-style-type: none"> <1% Forward/Reverse Phase 1% Forward/Reverse Phase 5% Forward/Reverse Phase 5% 0-10v 0.1% 0-10v 1% 0-10v 0.1% DALI 1% DALI 0.1% EcoSystem 1% EcoSystem 	<ul style="list-style-type: none"> <1% Forward/Reverse Phase 1% Forward/Reverse Phase 0.1% 0-10v 1% 0-10v 0.1% DALI 1% DALI 0.1% DALI 2-Channel* 0.1% DMX 2-Channel* 0.1% 0-10v 2-Channel* 0.1% EcoSystem <p><small>*Available with Tunable White LED option</small></p>
TRIM OPTIONS	<ul style="list-style-type: none"> 1-3/4" and 2-3/4" Aperture Square and Round Flanged and Flangeless Flat, Bevel, and Inset 	<ul style="list-style-type: none"> 2" Aperture Square and Round Flanged and Flangeless Flat 	<ul style="list-style-type: none"> 1-7/8", 2-1/4", and 2-3/4" (wall wash) Aperture Square and Round Flanged and Flangeless Flat, Bevel, and Wall Wash 	N/A
FINISH OPTIONS	<ul style="list-style-type: none"> White Pewter Satin Nickel Oil-Rubbed Bronze Black 	<ul style="list-style-type: none"> White Oil-Rubbed Bronze 	<ul style="list-style-type: none"> White Oil-Rubbed Bronze Satin Aluminum Satin Aluminum w/ White Flange 	<ul style="list-style-type: none"> White Pewter Satin Nickel Oil-Rubbed Bronze Black
WET LOCATION	✓	✓	✓	—
WARRANTY	5 Year Limited	5 Year Limited	5 Year Limited	5 Year Limited



All No. 8 Lighting fixtures and components are UL Listed to both U.S. and Canadian requirements. No. 8 Lighting trims and lamp modules are protected by one or more U.S. Patents. No. 8 Lighting reserves the right to change details of design, materials, and finish.
© 2025 No. 8 Lighting

