

Photometric / Colorimetric / Electric Report

Fixture Model:

202-R-BV-WD-7-60-NSP-PR1-2-FLR-2-BV

Trim Model:

Date:

7/17/2026



Light efficiency:

71 Lumen/Watt

Light quality:

CRI: 92.0

Color temperature:

2971 K

CIE 1931:

x: 0.435
y: 0.397


Output: 954 lm

Peak: 1154 cd



Power: 13.4 W

PF: 0.99

Spectra:





Color Details



TM-30: 89.4

CRI: 92.0 (R1-R8)



CRI R Values:

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
93.6	94.5	92.3	92.3	92.0	91.5	93.4	86.7	68.4	84.5	91.6	76.1	93.7	94.6	91.8


TM30 C Values:

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
92.0	91.9	84.7	88.7	91.2	89.8	90.5	92.8	94.0	88.5	83.7	86.0	91.9	88.6	91.3	86.1

CQS Q values:

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
89.4	97.2	82.1	83.6	88.5	87.1	84.2	89.6	95.4	89.2	88.8	89.8	91.7	89.2	88.9

CQS: 88.2



Color Parameters:

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2971 K	92.0	68.4	89.4	102.7	88.2	0.435	0.397	0.253	0.345	-0.0027

TM-30 Details







Rf 89.4

Fidelity index Rf


Rg 102.7

Gamut index Rg

Hue Bin	R _f	Shifts (%)	
		Chroma	Hue
1	92	-4%	-1%
2	92	-3%	3%
3	85	0%	8%
4	89	2%	6%
5	91	5%	5%
6	90	7%	-1%
7	90	2%	-6%
8	93	0%	-5%
9	94	-3%	0%
10	89	-4%	6%
11	84	-1%	12%
12	86	5%	7%
13	92	6%	0%
14	89	8%	-5%
15	91	2%	-5%
16	86	1%	-11%



Beam Details



Beam Intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
1141lx	285lx	127lx	71lx	46lx	32lx	23lx	18lx	14lx	11lx	9lx	8lx	7lx	6lx	5lx	4lx	4lx	4lx	3lx	3lx
106fc	26.5fc	11.8fc	6.6fc	4.2fc	2.9fc	2.2fc	1.7fc	1.3fc	1.1fc	0.9fc	0.7fc	0.6fc	0.5fc	0.5fc	0.4fc	0.4fc	0.3fc	0.3fc	0.3fc

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1141	1143	1147	1151	1153	1152	1145	1130	1106	1071	1023	955	866	760	647	508	351	220	139	97
100%	100%	100%	101%	101%	101%	100%	99%	97%	94%	90%	84%	76%	67%	57%	45%	31%	19%	12%	8%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1141	1143	1147	1151	1153	1152	1145	1130	1106	1071	1023	955	866	760	647	508	351	220	139	97
100%	100%	100%	101%	101%	101%	100%	99%	97%	94%	90%	84%	76%	67%	57%	45%	31%	19%	12%	8%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1141	1143	1147	1151	1153	1152	1145	1130	1106	1071	1023	955	866	760	647	508	351	220	139	97
100%	100%	100%	101%	101%	101%	100%	99%	97%	94%	90%	84%	76%	67%	57%	45%	31%	19%	12%	8%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1141	1143	1147	1151	1153	1152	1145	1130	1106	1071	1023	955	866	760	647	508	351	220	139	97
100%	100%	100%	101%	101%	101%	100%	99%	97%	94%	90%	84%	76%	67%	57%	45%	31%	19%	12%	8%

Beam angle 50%	Field angle 10%	Cut-off angle 2.5%	Intensity ratio in 120°	Intensity ratio in 90°
58.3°	73.7°	89°	98.8%	97.8%