

Photometric / Colorimetric / Electric Report

Fixture Model:

202-R-HI-30-15-PR1-2-FLR-2

Trim Model:

Date:

7/10/2026



Light efficiency:

58 Lumen/Watt

Light quality:

CRI: 93.3

Color temperature:

3039 K

CIE 1931:

x: 0.434
y: 0.402


Output: 798 lm

Peak: 6489 cd



Power: 13.7 W

PF: 0.95


Spectra:




Color Details



TM-30: 91.9



CRI: 93.3 (R1-R8)



CRI R Values:

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
94.0	95.4	95.0	94.2	93.1	93.7	94.3	86.4	67.4	88.0	94.5	79.0	94.3	96.4	91.1


TM30 C Values:

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
92.4	93.3	89.4	93.4	93.3	94.2	93.9	96.9	95.1	89.8	87.3	89.3	93.3	89.4	90.7	87.1

CQS Q values:

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
90.5	97.1	86.7	87.8	91.4	91.0	89.7	92.7	96.9	92.7	92.6	93.0	93.4	89.2	89.4

CQS: 91.1



Color Parameters:

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3039 K	93.3	67.4	91.9	100.9	91.1	0.434	0.402	0.249	0.347	-0.0004

TM-30 Details







Rf 91.9

Fidelity index Rf


Rg 100.9

Gamut index Rg

Hue Bin	R _f	Shifts (%)	
		Chroma	Hue
1	92	-4%	-1%
2	93	-3%	2%
3	89	-1%	5%
4	93	1%	4%
5	93	1%	3%
6	94	4%	0%
7	94	0%	-3%
8	97	0%	-2%
9	95	-2%	1%
10	90	-2%	5%
11	87	1%	9%
12	89	5%	4%
13	93	4%	-2%
14	89	6%	-6%
15	91	1%	-6%
16	87	0%	-10%



Beam Details



Beam Intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
6489lx	1622lx	721lx	406lx	260lx	180lx	132lx	101lx	80lx	65lx	54lx	45lx	38lx	33lx	29lx	25lx	22lx	20lx	18lx	16lx
602.8fc	150.7fc	67fc	37.7fc	24.1fc	16.7fc	12.3fc	9.4fc	7.4fc	6fc	5fc	4.2fc	3.6fc	3.1fc	2.7fc	2.4fc	2.1fc	1.9fc	1.7fc	1.5fc

Intensities in 0° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
6489	6357	6023	5588	5163	4773	4357	3896	3413	2962	2582	2232	1888	1575	1302	1067	864	691	549	440
100%	98%	93%	86%	80%	74%	67%	60%	53%	46%	40%	34%	29%	24%	20%	16%	13%	11%	8%	7%

Intensities in 90° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
6489	6357	6023	5588	5163	4773	4357	3896	3413	2962	2582	2232	1888	1575	1302	1067	864	691	549	440
100%	98%	93%	86%	80%	74%	67%	60%	53%	46%	40%	34%	29%	24%	20%	16%	13%	11%	8%	7%

Intensities in 180° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
6489	6357	6023	5588	5163	4773	4357	3896	3413	2962	2582	2232	1888	1575	1302	1067	864	691	549	440
100%	98%	93%	86%	80%	74%	67%	60%	53%	46%	40%	34%	29%	24%	20%	16%	13%	11%	8%	7%

Intensities in 270° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
6489	6357	6023	5588	5163	4773	4357	3896	3413	2962	2582	2232	1888	1575	1302	1067	864	691	549	440
100%	98%	93%	86%	80%	74%	67%	60%	53%	46%	40%	34%	29%	24%	20%	16%	13%	11%	8%	7%

Beam angle 50%	Field angle 10%	Cut-off angle 2.5%	Intensity ratio in 120°	Intensity ratio in 90°
16.7°	34.5°	48.7°	99.1%	98.8%