

Photometric / Colorimetric / Electric Report

Fixture Model:

202-S-BV-WD-5-25-NSP-PR1-2-FLS-2-BV

Trim Model:

Date:

8/5/2026



Light efficiency:

61 Lumen/Watt

Light quality:

CRI: 94.2

Color temperature:

3052 K

CIE 1931:

x: 0.430
y: 0.396


Output: 824 lm

Peak: 2902 cd



Power: 13.5 W

PF: 0.99


Spectra:




Color Details



TM-30: 91.2



CRI: 94.2 (R1-R8)



CRI R Values:

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
96.2	95.9	92.4	94.7	94.5	93.1	95.6	91.5	78.8	87.5	93.9	76.5	96.1	94.6	95.1


TM30 C Values:

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
94.1	94.4	88.6	91.9	91.7	92.3	94.0	95.2	94.9	87.5	84.7	87.4	93.4	90.0	91.6	87.4

CQS Q values:

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
93.0	97.5	83.7	85.1	90.5	90.2	86.9	91.8	95.2	90.9	91.1	92.5	94.2	92.4	92.3

CQS: 90.4



Color Parameters:

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3052 K	94.2	78.8	91.2	102.4	90.4	0.430	0.396	0.250	0.345	-0.0023

TM-30 Details







Rf 91.2

Fidelity index Rf


Rg 102.4

Gamut index Rg

Hue Bin	R _f	Shifts (%)	
		Chroma	Hue
1	94	-3%	-1%
2	94	-2%	2%
3	89	0%	6%
4	92	1%	5%
5	92	1%	4%
6	92	5%	0%
7	94	1%	-3%
8	95	0%	-3%
9	95	-2%	2%
10	88	-3%	7%
11	85	1%	11%
12	87	5%	6%
13	93	5%	0%
14	90	7%	-4%
15	92	2%	-5%
16	87	2%	-10%



Beam Details



Beam Intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
2902lx	726lx	322lx	181lx	116lx	81lx	59lx	45lx	36lx	29lx	24lx	20lx	17lx	15lx	13lx	11lx	10lx	9lx	8lx	7lx
269.6fc	67.4fc	30fc	16.9fc	10.8fc	7.5fc	5.5fc	4.2fc	3.3fc	2.7fc	2.2fc	1.9fc	1.6fc	1.4fc	1.2fc	1.1fc	0.9fc	0.8fc	0.7fc	0.7fc

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2902	2869	2759	2589	2367	2095	1785	1450	1126	838	611	447	335	260	205	164	132	106	85	69
100%	99%	95%	89%	82%	72%	62%	50%	39%	29%	21%	15%	12%	9%	7%	6%	5%	4%	3%	2%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2902	2869	2759	2589	2367	2095	1785	1450	1126	838	611	447	335	260	205	164	132	106	85	69
100%	99%	95%	89%	82%	72%	62%	50%	39%	29%	21%	15%	12%	9%	7%	6%	5%	4%	3%	2%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2902	2869	2759	2589	2367	2095	1785	1450	1126	838	611	447	335	260	205	164	132	106	85	69
100%	99%	95%	89%	82%	72%	62%	50%	39%	29%	21%	15%	12%	9%	7%	6%	5%	4%	3%	2%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2902	2869	2759	2589	2367	2095	1785	1450	1126	838	611	447	335	260	205	164	132	106	85	69
100%	99%	95%	89%	82%	72%	62%	50%	39%	29%	21%	15%	12%	9%	7%	6%	5%	4%	3%	2%

Beam angle 50%	Field angle 10%	Cut-off angle 2.5%	Intensity ratio in 120°	Intensity ratio in 90°
28°	50.2°	75°	99.0%	97.6%