

Photometric / Colorimetric / Electric Report

Fixture Model:
202-S-BV-WD-7-60-NSP-PR1-2-FLS-2-BV
Trim Model:

Date:
8/11/2026



Light efficiency:
74 Lumen/Watt


Light quality:
CRI: 92.1

Color temperature:
2969 K



CIE 1931:
x: 0.435
y: 0.397

Output:	996 lm
Peak:	1139 cd
Power:	13.5 W
PF:	0.99

Spectra:





Color Details



TM-30: 89.4

CRI: 92.1 (R1-R8)



CRI R Values:

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
93.6	94.5	92.3	92.4	92.0	91.5	93.4	86.7	68.5	84.5	91.7	76.1	93.7	94.6	91.8


TM30 C Values:

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
92.1	91.9	84.8	88.7	91.2	89.7	90.4	92.8	94.0	88.6	83.7	86.0	91.9	88.7	91.3	86.1

CQS Q values:

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
89.4	97.2	82.2	83.7	88.6	87.1	84.2	89.7	95.3	89.2	88.9	89.9	91.8	89.2	88.9

CQS: 88.3



Color Parameters:

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2969 K	92.1	68.5	89.4	102.7	88.3	0.435	0.397	0.253	0.346	-0.0027

TM-30 Details







Rf 89.4

Fidelity index Rf


Rg 102.7

Gamut index Rg

Hue Bin	R _f	Shifts (%)	
		Chroma	Hue
1	92	-4%	-1%
2	92	-3%	3%
3	85	0%	8%
4	89	2%	6%
5	91	5%	5%
6	90	7%	-1%
7	90	2%	-6%
8	93	0%	-5%
9	94	-3%	-1%
10	89	-4%	6%
11	84	-1%	12%
12	86	5%	7%
13	92	6%	0%
14	89	8%	-5%
15	91	2%	-5%
16	86	1%	-11%



Beam Details



Beam Intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
1131lx	283lx	126lx	71lx	45lx	31lx	23lx	18lx	14lx	11lx	9lx	8lx	7lx	6lx	5lx	4lx	4lx	3lx	3lx	3lx
105fc	26.3fc	11.7fc	6.6fc	4.2fc	2.9fc	2.1fc	1.6fc	1.3fc	1.1fc	0.9fc	0.7fc	0.6fc	0.5fc	0.5fc	0.4fc	0.4fc	0.3fc	0.3fc	0.3fc

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1131	1131	1135	1138	1139	1135	1124	1105	1077	1039	988	925	845	753	651	537	411	301	218	161
100%	100%	100%	101%	101%	100%	99%	98%	95%	92%	87%	82%	75%	67%	58%	48%	36%	27%	19%	14%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1131	1131	1135	1138	1139	1135	1124	1105	1077	1039	988	925	845	753	651	537	411	301	218	161
100%	100%	100%	101%	101%	100%	99%	98%	95%	92%	87%	82%	75%	67%	58%	48%	36%	27%	19%	14%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1131	1131	1135	1138	1139	1135	1124	1105	1077	1039	988	925	845	753	651	537	411	301	218	161
100%	100%	100%	101%	101%	100%	99%	98%	95%	92%	87%	82%	75%	67%	58%	48%	36%	27%	19%	14%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1131	1131	1135	1138	1139	1135	1124	1105	1077	1039	988	925	845	753	651	537	411	301	218	161
100%	100%	100%	101%	101%	100%	99%	98%	95%	92%	87%	82%	75%	67%	58%	48%	36%	27%	19%	14%

Beam angle 50%	Field angle 10%	Cut-off angle 2.5%	Intensity ratio in 120°	Intensity ratio in 90°
58.9°	80.2°	93.2°	99.0%	97.4%