

Photometric / Colorimetric / Electric Report

Fixture Model:

202-S-WD-6-25-NSP-PR1-2-FLS-2

Trim Model:

Date:

8/11/2026



Light efficiency:

53 Lumen/Watt

Light quality:

CRI: 92.2

Color temperature:

2786 K

CIE 1931:

**x: 0.453
y: 0.409**


Output: 715 lm

Peak: 2751 cd



Power: 13.5 W

PF: 0.99


Spectra:




Color Details



TM-30: 90.6



CRI: 92.2 (R1-R8)



CRI R Values:

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
93.4	94.2	92.5	93.4	91.9	91.9	94.2	86.3	67.0	84.4	93.2	77.6	93.4	94.7	90.6


TM30 C Values:

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
92.1	92.6	87.0	90.3	92.2	91.1	90.6	93.6	94.4	90.7	86.4	88.2	92.4	89.5	91.4	87.4

CQS Q values:

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
88.6	96.7	85.2	86.6	89.4	87.3	86.0	90.8	95.6	90.8	91.2	92.2	93.0	88.6	88.2

CQS: 89.4



Color Parameters:

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2786 K	92.2	67.0	90.6	101.9	89.4	0.453	0.409	0.259	0.350	-0.0002

TM-30 Details







Rf 90.6

Fidelity index Rf


Rg 101.9

Gamut index Rg

Hue Bin	R _f	Shifts (%)	
		Chroma	Hue
1	92	-4%	-1%
2	93	-3%	3%
3	87	-1%	7%
4	90	2%	6%
5	92	5%	5%
6	91	6%	-1%
7	91	2%	-6%
8	94	0%	-4%
9	94	-3%	-1%
10	91	-4%	4%
11	86	-1%	10%
12	88	5%	5%
13	92	5%	-1%
14	89	6%	-5%
15	91	2%	-5%
16	87	0%	-10%



Beam Details



Beam Intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
2751lx	688lx	306lx	172lx	110lx	76lx	56lx	43lx	34lx	28lx	23lx	19lx	16lx	14lx	12lx	11lx	10lx	8lx	8lx	7lx
255.6fc	63.9fc	28.4fc	16fc	10.2fc	7.1fc	5.2fc	4fc	3.2fc	2.6fc	2.1fc	1.8fc	1.5fc	1.3fc	1.1fc	1fc	0.9fc	0.8fc	0.7fc	0.6fc

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2751	2716	2614	2449	2229	1959	1646	1314	999	730	522	375	275	206	158	121	94	73	56	44
100%	99%	95%	89%	81%	71%	60%	48%	36%	27%	19%	14%	10%	7%	6%	4%	3%	3%	2%	2%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2751	2716	2614	2449	2229	1959	1646	1314	999	730	522	375	275	206	158	121	94	73	56	44
100%	99%	95%	89%	81%	71%	60%	48%	36%	27%	19%	14%	10%	7%	6%	4%	3%	3%	2%	2%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2751	2716	2614	2449	2229	1959	1646	1314	999	730	522	375	275	206	158	121	94	73	56	44
100%	99%	95%	89%	81%	71%	60%	48%	36%	27%	19%	14%	10%	7%	6%	4%	3%	3%	2%	2%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2751	2716	2614	2449	2229	1959	1646	1314	999	730	522	375	275	206	158	121	94	73	56	44
100%	99%	95%	89%	81%	71%	60%	48%	36%	27%	19%	14%	10%	7%	6%	4%	3%	3%	2%	2%

Beam angle 50%	Field angle 10%	Cut-off angle 2.5%	Intensity ratio in 120°	Intensity ratio in 90°
27.3°	48°	68.8°	99.4%	98.5%