No. 8 Lighting **LED** Product Comparison Guide

	800 SERIES	400 SERIES	200 SERIES	MPT3 SERIES
MOUNTING TYPE	RECESSED	RECESSED	RECESSED	SURFACE MOUNTED
APPLICATION	NEW CONSTRUCTION	NEW CONSTRUCTION or REMODEL	NEW CONSTRUCTION or REMODEL	NEW CONSTRUCTION or REMODEL
HOUSING/ CONFIGURATION OPTIONS	• 2-1/8"H Single and Multi-Lamp IC/Airtight/CP-Rated (805) • 4"H Single and Multi-Lamp IC/Airtight/CP-Rated (804S)	• 4-7/8"H Single Lamp IC/Airtight • 5-3/8"H Single Lamp IC/Airtight/CP-Rated	• 4-1/4"H Single Lamp Non-IC/Airtight (202 and 203) • 4-3/8"H Single Lamp IC/Airtight/CP-Rated (202 and 203) • 5"H Single Lamp Non-IC (200HD) • 5- 3/8"H Single Lamp IC/Airtight/CP Rated (200-HD)	• 2- 1/2" Square and Round Housing Options with 1- 3/4" Aperture • 2- 1/2" and 4" Square and Round Canopy Options • Ceiling or Wall Mount • Four Stem Length Options
CA JA8 COMPLIANT	✓	✓	w/ IC-CP Housing Option	✓
LED OPTIONS	• Static White: 2700K and 3000K • Warm Dimming: 3000-1800K, 2800-2200K, and 3000-2200K • Tunable White: 4700-2200K	• Static White: 2700K and 3000K • Warm Dimming: 3000-1800K, 2800-2200K, and 3000-2200K	• Static White: 2700K, 3000K, 3500K, and 4000K • Warm Dimming: 3000-1800K, 2800-2200K, and 3000-2200K	• Static White: 2700K and 3000K • Warm Dimming: 3000-1800K 2800-2200K, and 3000-2200K • Tunable White: 4700- 2200K
DELIVERED LUMENS @ 3000K CCT	• Static White: 1093-4164 lm • Warm Dimming: 951-3472 lm • Tunable White: 1018-4072 lm	• Static White: 1082 lm • Warm Dimming: 864 lm	• Static White: 1197-2026 lm • Warm Dimming: 996 lm	• Static White: 1220-1489 lm • Warm Dimming: 1057 lm • Tunable White: 1087 lm
DELIVERED EFFICACY @ 3000K CCT	• Static White: 71-79 lpw • Warm Dimming: 60-65 lpw • Tunable White: 64-73 lpw	• Static White: 75 lpw • Warm Dimming: 59 lpw	• Static White: 79-90 lpw • Warm Dimming: 74 lpw	• Static White: 75-85 lpw • Warm Dimming: 73 lpw • Tunable White: 72 lpw
LAMP MODULE OPTIONS	• Adjustable Accent/Wall Wash (0°- 45°) • Adjustable Accent/Wall Wash (0°- 35°) • Fixed Downlight • Fixed Wall Wash • Adjustable Mirror Reflector (35°-90°)	• Adjustable Accent/Wall Wash (0°- 35°)	• Adjustable Accent/Wall Wash (0°-30°) • Fixed Wall Wash	• Position 1: Adjustable (0°- 110°) Wall or Ceiling Mount • Position 2: Adjustable (0°- 50°) Wall or Ceiling Mount • Position 3: Fixed (0°) Ceiling Mount Note: Positions 1-3 can be set before or after installation.
OPTIC OPTIONS	• 10°, 15°, 25°, and 40° • Beam enhancing lenses: Narrow, Medium, Wide, Extra Wide, and Linear Spread • Color filtering lenses: 2400K, 2700K, and 3500K	• 10°, 15°, 25°, and 40° • Beam enhancing lenses: Narrow, Medium, Wide, Extra Wide, and Linear Spread • Color filtering lenses: 2400K, 2700K, and 3500K	• 15°, 25°, 40°, and 60° • Beam enhancing lenses: Narrow, Medium, Wide, Extra Wide, and Linear Spread	• 10°, 15°, 25°, and 40° • Beam enhancing lenses: Narrow, Medium, Wide, Extra Wide, Linear Spread, and HEX Louver • Color filtering lenses: 2400K, 2700K, and 3500K
DRIVER OPTIONS	• <1% Forward/Reverse Phase • 0.1% 0 -10v • 1% 0 -10v • 0.1% DALI • 1% DALI • 0.1% DALI 2-Channel* • 0.1% DMX 2-Channel* • 0.1% 0-10v 2-Channel* • 0.1% EcoSystem • 1% EcoSystem *Available with Tunable White LED option	• <1% Forward/Reverse Phase • 0.1% 0 -10v • 1% 0 -10v • 0.1% DALI • 1% DALI • 1% Forward Phase • 0.1% EcoSystem • 1% EcoSystem	• <1% Forward/Reverse Phase • 1% Forward/Reverse Phase • 5% Forward/Reverse Phase • 5% 0-10v • 0.1% 0 -10v • 1% 0 -10v • 0.1% DALI • 1% DALI • 0.1% EcoSystem • 1% EcoSystem	• <1% Forward/Reverse Phase • 1% Forward/Reverse Phase • 0.1% 0 -10v • 1% 0 -10v • 0.1% DALI • 1% DALI • 0.1% DALI 2-Channel* • 0.1% DMX 2-Channel* • 0.1% 0-10v 2-Channel* • 0.1% EcoSystem *Available with Tunable White LED option
TRIM OPTIONS	• 1-3/4" and 2-3/4" Aperture • Square and Round • Flanged and Flangeless • Flat, Bevel, and Inset	• 2" Aperture • Square and Round • Flanged and Flangeless • Flat	• 1-7/8", 2-1/4", and 2-3/4" (wall wash) Aperture • Square and Round • Flanged and Flangeless • Flat, Bevel, and Wall Wash	N/A
FINISH OPTIONS	• White • Pewter • Satin Nickel • Oil-Rubbed Bronze • Black	• White • Oil-Rubbed Bronze	• White • Oil-Rubbed Bronze • Satin Aluminum • Satin Aluminum w/ White Flange	• White • Pewter • Satin Nickel • Oil-Rubbed Bronze • Black
WET LOCATION	✓	✓	✓	–
WARRANTY	5 Year Limited	5 Year Limited	5 Year Limited	5 Year Limited

526 Portal Street
Cotati, CA 94931
USA
P 707.794.0888
www.8lighting.com

All No. 8 Lighting fixtures and components are UL Listed to both U.S. and Canadian requirements. No. 8 Lighting trims and lamp modules are protected by one or more U.S. Patents. No. 8 Lighting reserves the right to change details of design, materials, and finish.
© 2026 No. 8 Lighting

9/2026

93301-09