DIMMER COMPATIBILITY
800 SERIES
DRIVER MODELS: PR1-8, PR1-8.5
LED MODELS: HI, HI-2, HI-3, WD/WD-2/WD-4

www.8lighting.com

No.8 Lighting Driver Model and Output	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Adjust (Vantage Only)	Dimming Range	
								High-End (%)	Low-End (%)		High-End (%)	Low-End (%)
PR1-8, PR1-8.5												
PR1-8/8.5-1000	**HI**	Crestron	Cameo Express Wireless	CLW-DIMEX-E	120	Forward Phase	Wallbox/System	75.0	3.0		**100.0%**	**3.0%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							75.0	5.0		**100.0%**	**1.0%**
PR1-8/8.5-1400	**HI**							75.0	10.0		**100.0%**	**7.0%**
PR1-8/8.5-1000	**HI**	Crestron	Cameo Wireless	CLW-DIMEX-P	120	Forward Phase	Wallbox/System	75.0	3.0		**100.0%**	**3.0%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							75.0	5.0		**100.0%**	**1.0%**
PR1-8/8.5-1400	**HI**							75.0	10.0		**100.0%**	**7.0%**
PR1-8/8.5-1000	**HI**	Crestron	Cameo Express Wireless	CLW-DIMSWEX-E	120	Forward Phase	Wallbox/System	75.0	3.0		**100.0%**	**3.0%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							75.0	5.0		**100.0%**	**1.0%**
PR1-8/8.5-1400	**HI**							75.0	10.0		**100.0%**	**7.0%**
PR1-8/8.5-1000	**HI**	Crestron	Cameo Wireless	CLW-DIMSWEX-P	120	Forward Phase	Wallbox/System	75.0	3.0		**100.0%**	**3.0%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							75.0	5.0		**100.0%**	**1.0%**
PR1-8/8.5-1400	**HI**							75.0	10.0		**100.0%**	**7.0%**
PR1-8/8.5-1000	**HI**	Crestron	Cameo Wireless	CLW-DIMUEX-P	120	Forward or Reverse Phase	Wallbox/System	80.0	3.0		**100.0%**	**1.0%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							85.0	20.0		**100.0%**	**1.0%**
PR1-8/8.5-1400	**HI**							80.0	1.0		**100.0%**	**1.0%**
PR1-8/8.5-1000	**HI**	Crestron		CLX-1DIMU4	120	Forward or Reverse Phase	Residential/ Commercial System	80.0	5.0		**100.0%**	**1.0%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							85.0	20.0		**100.0%**	**1.0%**
PR1-8/8.5-1400	**HI**							80.0	25.0		**100.0%**	**5.0%**
PR1-8/8.5-1000	**HI**	Crestron		CLX-2DIMU8	120	Forward or Reverse Phase	Residential/ Commercial System	80.0	5.0		**100.0%**	**1.0%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							85.0	20.0		**100.0%**	**1.0%**
PR1-8/8.5-1400	**HI**							80.0	25.0		**100.0%**	**5.0%**
PR1-8/8.5-1000	**HI**	Crestron	Wireless Horizon	HZ-DIMEX SERIES	120	Forward Phase	Wallbox/System	80.0	10.0		**100.0%**	**1.0%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							85.0	15.0		**100.0%**	**1.0%**
PR1-8/8.5-1400	**HI**							80.0	3.0		**100.0%**	**1.0%**
PR1-8/8.5-1000	**HI**	Crestron	Wireless Horizon	HZ-DIMUEX SERIES	120	Forward or Reverse Phase	Wallbox/System	80.0	10.0		**100.0%**	**2.0%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							85.0	15.0		**100.0%**	**1.0%**
PR1-8/8.5-1400	**HI**							80.0	3.0		**100.0%**	**1.0%**
PR1-8/8.5-1000	**HI**	Crestron		P-DIMEX	120		Wallbox/System	75.0	3.0		**100.0%**	**3.0%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							75.0	5.0		**100.0%**	**1.0%**
PR1-8/8.5-1400	**HI**							75.0	10.0		**100.0%**	**7.0%**
PR1-8/8.5-1000	**HI**	Crestron	Zum Wireless	ZUMMESH-DELV	120	Reverse Phase	Wallbox/System	80.0	10.0		**100.0%**	**1.0%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							80.0	25.0		**100.0%**	**1.0%**
PR1-8/8.5-1400	**HI**							85.0	9.0		**100.0%**	**1.0%**
PR1-8/8.5-1000	**HI**	Crestron	Zum Wireless	ZUMMESH-DIM	120	Forward Phase	Wallbox/System	80.0	20.0		**100.0%**	**8.0%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							80.0	25.0		**100.0%**	**2.0%**
PR1-8/8.5-1400	**HI**							80.0	15.0		**100.0%**	**5.0%**
PR1-8/8.5-1000	**HI**	Crestron	Zum Wireless	ZUMMESH-EXP-16A-DIMU	120	Forward or Reverse Phase	Wallbox/System	80.0	15.0		**100.0%**	**3.0%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							85.0	20.0		**100.0%**	**1.0%**
PR1-8/8.5-1400	**HI**							80.0	14.0		**100.0%**	**1.0%**
PR1-8/8.5-350	**HI-3**	Lutron	Caseta	PD-5NE	120	Reverse Phase	Wallbox	High & Low-End Trim Required			**93.2%**	**0.3%**
PR1-8/8.5-1000	**HI-2**										**99.9%**	**0.3%**
PR1-8/8.5-1000	**HI**										**99.9%**	**0.1%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**100.0%**	**0.0%**
PR1-8/8.5-1400	**HI**										**99.6%**	**0.1%**
PR1-8/8.5-350	**HI-3**	Lutron	Caseta	PD-6WCL	120	Forward Phase	Wallbox	High & Low-End Trim Required			**99.0%**	**0.7%**
PR1-8/8.5-1000	**HI-2**										**100.0%**	**0.3%**
PR1-8/8.5-1000	**HI**										**100.0%**	**0.4%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**95.2%**	**0.0%**
PR1-8/8.5-350	**HI-3**	Lutron	Caseta	PD-10NXD	120	Forward Phase	Wallbox	High & Low-End Trim Required			**98.5%**	**1.0%**
PR1-8/8.5-1000	**HI-2**										**100.0%**	**0.1%**
PR1-8/8.5-1000	**HI**										**100.0%**	**0.6%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**95.1%**	**0.0%**
PR1-8/8.5-1400	**HI**										**100.0%**	**0.6%**
PR1-8/8.5-350	**HI-3**	Lutron	Diva	DVCL-253PH	120	Forward Phase	Wallbox	High & Low-End Trim Required			**99.6%**	**0.7%**
PR1-8/8.5-1000	**HI-2**										**100.0%**	**0.4%**
PR1-8/8.5-1000	**HI**										**100.0%**	**0.3%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**98.4%**	**4.3%**
PR1-8/8.5-1400	**HI**										**100.0%**	**0.4%**
PR1-8/8.5-350	**HI-3**	Lutron	Grafik Eye 3000	GRX-3506	120	Forward Phase	Residential/ Commercial System	High & Low-End Trim Required			**98.8%**	**2.1%**
PR1-8/8.5-1000	**HI-2**										**100.0%**	**0.8%**
PR1-8/8.5-1000	**HI**										**100.0%**	**0.5%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**93.4%**	**0.1%**
PR1-8/8.5-1400	**HI**										**100.0%**	**3.0%**
PR1-8/8.5-350	**HI-3**	Lutron	Grafik Eye QS	QSGRJ-4P	120	Forward Phase	Residential/ Commercial System	100	3.0		**98.7%**	**0.8%**
PR1-8/8.5-1000	**HI-2**							79.0	1.0		**100.0%**	**1.1%**
PR1-8/8.5-1000	**HI**							80.0	5.0		**100.0%**	**0.4%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							100.0	8.0		**99.3%**	**0.2%**
PR1-8/8.5-1400	**HI**							79.0	5.0		**100.0%**	**0.6%**
PR1-8/8.5-350	**HI-3**	Lutron	Homeworks QS	HQRA-PRO	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			**99.2%**	**1.1%**
PR1-8/8.5-1000	**HI-2**										**100.0%**	**0.6%**
PR1-8/8.5-1000	**HI**										**100.0%**	**0.5%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**98.3%**	**0.1%**
PR1-8/8.5-1400	**HI**										**100.0%**	**0.8%**

No.8 Lighting Driver Model and Output	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Adjust (Vantage Only)	Dimming Range	
								High-End (%)	Low-End (%)		High-End (%)	Low-End (%)
PR1-8/8.5 (Continued)												
PR1-8/8.5-350	**HI-3**	Lutron	Homeworks QS	HQRA-PRO	120	Reverse Phase	Wallbox/System	High & Low-End Trim Required			**94.9%**	**0.2%**
PR1-8/8.5-1000	**HI-2**										**100.0%**	**0.6%**
PR1-8/8.5-1000	**HI**										**100.0%**	**0.4%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**89.1%**	**0.1%**
PR1-8/8.5-1400	**HI**										**100.0%**	**0.4%**
PR1-8/8.5-350	**HI-3**	Lutron	Homeworks QS	HQRD-10ND	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			**96.0%**	**1.7%**
PR1-8/8.5-1000	**HI-2**										**100.0%**	**0.6%**
PR1-8/8.5-1000	**HI**										**100.0%**	**1.7%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**98.0%**	**0.1%**
PR1-8/8.5-1400	**HI**										**100.0%**	**4.5%**
PR1-8/8.5-1000*	**HI-2**	Lutron	Homeworks QSX	LQSE-4A-120-D*	120	Forward Phase	Residential/ Commercial System	80.0	1.0		**100.0%**	**0.7%**
PR1-8/8.5-1000*	**HI**							79.0	1.0		**100.0%**	**0.6%**
PR1-8/8.5-350*	**WD/WD-2/WD-4**							97.0	9.0		**99.4%**	**0.1%**
PR1-8/8.5-1400*	**HI**							78.0	1.0		**100.0%**	**0.9%**
PR1-8/8.5-1000*	**HI-2**	Lutron	Homeworks QSX	LQSE-4A-120-D*	120	Reverse Phase	Residential/ Commercial System	84.0	5.0		**100.0%**	**0.2%**
PR1-8/8.5-1000*	**HI**							83.0	5.0		**100.0%**	**0.2%**
PR1-8/8.5-350*	**WD/WD-2/WD-4**							98.0	38.0		**100.0%**	**0.1%**
PR1-8/8.5-1400*	**HI**							85.0	4.0		**100.0%**	**0.2%**
PR1-8/8.5-350	**HI-3**	Lutron	Homeworks QSX	LQSE-4A5-120-D	120	Forward Phase	Residential/ Commercial System	100.0	1.0		**100.0%**	**1.0%**
PR1-8/8.5-1000	**HI-2**							80.0	2.0		**100.0%**	**0.7%**
PR1-8/8.5-1000	**HI**							80.0	1.0		**100.0%**	**0.6%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							97.0	9.0		**99.4%**	**0.1%**
PR1-8/8.5-1400	**HI**							80.0	1.0		**100.0%**	**0.9%**
PR1-8/8.5-350	**HI-3**	Lutron	Homeworks QSX	LQSE-4A5-120-D	120	Reverse Phase	Residential/ Commercial System	100.0	10.0		**99.9%**	**1.0%**
PR1-8/8.5-1000	**HI-2**							84.0	5.0		**100.0%**	**0.3%**
PR1-8/8.5-1000	**HI**							84.0	6.0		**100.0%**	**0.3%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							100.0	38.0		**100.0%**	**0.1%**
PR1-8/8.5-1400	**HI**							85.0	4.0		**100.0%**	**0.2%**
PR1-8/8.5-350	**HI-3**	Lutron	Maestro	MA-PRO-XX	120	Forward Phase	Wallbox	High & Low-End Trim Required			**98.7%**	**1.0%**
PR1-8/8.5-1000	**HI-2**										**100.0%**	**0.5%**
PR1-8/8.5-1000	**HI**										**100.0%**	**0.4%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**98.3%**	**0.1%**
PR1-8/8.5-1400	**HI**										**100.0%**	**4.4%**
PR1-8/8.5-350	**HI-3**	Lutron	Maestro	MA-PRO-XX	120	Reverse Phase	Wallbox	High & Low-End Trim Required			**98.1%**	**0.2%**
PR1-8/8.5-1000	**HI-2**										**100.0%**	**0.5%**
PR1-8/8.5-1000	**HI**										**92.1%**	**0.5%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**91.0%**	**0.1%**
PR1-8/8.5-1400	**HI**										**100.0%**	**0.2%**
PR1-8/8.5-350	**HI-3**	Lutron	Maestro	MACL-153M	120	Forward Phase	Wallbox	High & Low-End Trim Required			**97.9%**	**0.9%**
PR1-8/8.5-1000	**HI-2**										**100.0%**	**0.3%**
PR1-8/8.5-1000	**HI**										**100.0%**	**0.8%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**96.7%**	**0.1%**
PR1-8/8.5-1400	**HI**										**100.0%**	**0.1%**
PR1-8/8.5-350	**HI-3**	Lutron	Maestro	MRF2-6ELV-120	120	Reverse Phase	Wallbox	High & Low-End Trim Required			**97.1%**	**0.4%**
PR1-8/8.5-1000	**HI-2**										**100.0%**	**0.3%**
PR1-8/8.5-1000	**HI**										**100.0%**	**0.3%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**90.0%**	**0.1%**
PR1-8/8.5-1400	**HI**										**100.0%**	**0.1%**
PR1-8/8.5-350	**HI-3**	Lutron	Maestro	MRF2-6ND-120	120	Forward Phase	Wallbox	High & Low-End Trim Required			**98.8%**	**1.1%**
PR1-8/8.5-1000	**HI-2**										**100.0%**	**0.7%**
PR1-8/8.5-1000	**HI**										**100.0%**	**1.6%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**98.3%**	**0.0%**
PR1-8/8.5-1400	**HI**										**100.0%**	**1.7%**
PR1-8/8.5-350	**HI-3**	Lutron	Radio RA 2	RRD-6NA	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			**99.4%**	**2.2%**
PR1-8/8.5-1000	**HI-2**										**100.0%**	**0.4%**
PR1-8/8.5-1000	**HI**										**100.0%**	**0.3%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**90.3%**	**0.0%**
PR1-8/8.5-1400	**HI**										**100.0%**	**2.3%**
PR1-8/8.5-350	**HI-3**	Lutron	Radio RA 2	RRD-6NA	120	Reverse Phase	Wallbox/System	High & Low-End Trim Required			**97.6%**	**0.5%**
PR1-8/8.5-1000	**HI-2**										**100.0%**	**1.1%**
PR1-8/8.5-1000	**HI**										**100.0%**	**1.0%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**98.2%**	**0.1%**
PR1-8/8.5-1400	**HI**										**100.0%**	**0.1%**
PR1-8/8.5-350	**HI-3**	Lutron	Radio RA 2	RRD-10ND	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			**97.5%**	**1.5%**
PR1-8/8.5-1000	**HI-2**										**100.0%**	**0.7%**
PR1-8/8.5-1000	**HI**										**100.0%**	**4.1%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**98.1%**	**0.0%**
PR1-8/8.5-1400	**HI**										**100.0%**	**2.0%**
PR1-8/8.5-350	**HI-3**	Lutron	Radio RA 2	RRD-PRO	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			**99.0%**	**1.1%**
PR1-8/8.5-1000	**HI-2**										**100.0%**	**0.4%**
PR1-8/8.5-1000	**HI**										**100.0%**	**0.6%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**98.4%**	**0.0%**
PR1-8/8.5-1400	**HI**										**100.0%**	**4.1%**
PR1-8/8.5-350	**HI-3**	Lutron	Radio RA 2	RRD-PRO	120	Reverse Phase	Wallbox/System	High & Low-End Trim Required			**98.7%**	**0.9%**
PR1-8/8.5-1000	**HI-2**										**100.0%**	**0.5%**
PR1-8/8.5-1000	**HI**										**100.0%**	**0.5%**
PR1-8/8.5-350	**WD/WD-2/WD-4**										**88.8%**	**0.1%**
PR1-8/8.5-1400	**HI**										**100.0%**	**0.4%**
PR1-8/8.5-1000	**HI**	Vantage		ScenePoint	120	Forward Phase	Residential System	78.5	3.5	85	**94.9%**	**1.9%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							81.0	9.0	100	**95.0%**	**1.5%**
PR1-8/8.5-1400	**HI**							73.5	4.0	95	**95.1%**	**1.8%**
PR1-8/8.5-1000	**HI**	Vantage		SDM12-EM	120	Forward Phase	Residential System	75.4	2.0	85	**95.3%**	**1.2%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							77.5	7.0	100	**95.0%**	**1.2%**
PR1-8/8.5-1400	**HI**							68.0	2.5	95	**94.9%**	**2.4%**

No.8 Lighting Driver Model and Output	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Adjust (Vantage Only)	Dimming Range	
								High-End (%)	Low-End (%)		High-End (%)	Low-End (%)
PR1-8, PR1-8.5 (Continued)												
PR1-8/8.5-1000	**HI**	Vantage		UDM-FWD	120	Forward Phase	Residential System	78.2	3.0	85	**94.9%**	**1.5%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							79.5	7.0	100	**95.0%**	**0.9%**
PR1-8/8.5-1400	**HI**							72.0	3.5	100	**94.9%**	**2.3%**
PR1-8/8.5-1000	**HI**	Vantage		UDM-REV	120	Reverse Phase	Residential System	84.5	6.5	40	**95.4%**	**1.6%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							87.5	22.0	25	**95.3%**	**1.6%**
PR1-8/8.5-1400	**HI**							80.4	6.8	40	**95.1%**	**2.2%**
PR1-8/8.5-1000	**HI**	Vantage		UDS-F	120	Forward Phase	Wallbox/System	81.0	3.5	85	**95.0%**	**1.5%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							82.4	9.0	100	**94.6%**	**1.0%**
PR1-8/8.5-1400	**HI**							75.5	4.0	90	**95.1%**	**1.4%**
PR1-8/8.5-1000	**HI**	Vantage		UDS-R	120	Reverse Phase	Wallbox/System	82.4	4.5	40	**94.8%**	**1.2%**
PR1-8/8.5-350	**WD/WD-2/WD-4**							86.0	21.0	25	**94.8%**	**2.3%**
PR1-8/8.5-1400	**HI**							79.2	4.7	40	**95.0%**	**2.5%**

Dimmer compatibility testing performed using 120V/60Hz supply.

Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.

The design, specification, or performance of compatible dimmers is subject to change without notice.

***Maximum of four (4) drivers per output with Lutron LQSE-4A-120-D.**

For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93801-01-1 - 11/2025

DIMMER COMPATIBILITY
800 SERIES
DRIVER MODELS: EL1-8, EL1-8.5, EL1-01-8, EL1-01-8.5
LED MODELS: HI, HI-2, WD/WD-2/WD-4

www.8lighting.com

No.8 Lighting Driver Model and Output	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Adjust (Vantage Only)	Dimming Range	
								High-End (%)	Low-End (%)		High-End (%)	Low-End (%)
EL1-8												
EL1-8-1000	**HI-2**	Lutron	Diva	DVSTV-XX	120	0-10v	Wallbox	High & Low-End Trim Required			**100.0%**	**2.3%**
EL1-8-1000	**HI**										**100.0%**	**2.0%**
EL1-8-350	**WD/WD-2/WD-4**										**100.0%**	**0.9%**
EL1-8-1400	**HI**										**100.0%**	**2.3%**
EL1-8-1000	**HI-2**	Lutron	Homeworks QSX	LQSE-4T5-120-D	120	0-10v	Residential/ Commercial System	90.0	3.0		**100.0%**	**2.3%**
EL1-8-1000	**HI**							90.0	2.0		**100.0%**	**2.0%**
EL1-8-350	**WD/WD-2/WD-4**							90.0	3.0		**100.0%**	**0.9%**
EL1-8-1400	**HI**							90.0	2.0		**100.0%**	**2.2%**
EL1-8-1000	**HI-2**	Lutron	Nova T	NTSTV-DV-XX	120	0-10v	Wallbox	High & Low-End Trim Required			**100.0%**	**2.3%**
EL1-8-1000	**HI**										**100.0%**	**2.0%**
EL1-8-350	**WD/WD-2/WD-4**										**100.0%**	**0.9%**
EL1-8-1400	**HI**										**100.0%**	**2.2%**
EL1-8-1000	**HI**	Vantage		LVOS-0-10-PWM	120	0-10v	Residential/ Commercial System	7.8 (VDC)	1.4 (VDC)	100	**95.0%**	**2.1%**
EL1-8-350	**WD/WD-2/WD-4**							8.1 (VDC)	1.5 (VDC)	100	**95.2%**	**2.1%**
EL1-8-1400	**HI**							7.8 (VDC)	1.5 (VDC)	100	**94.7%**	**3.7%**
EL1-8.5												
EL1-8.5-1000	**HI-2**	Lutron	Diva	DVSTV-XX	120	0-10v	Wallbox	High & Low-End Trim Required			**99.9%**	**2.3%**
EL1-8.5-1000	**HI**										**100.0%**	**2.1%**
EL1-8.5-350	**WD/WD-2/WD-4**										**99.9%**	**1.1%**
EL1-8.5-1000	**HI-2**	Lutron	Homeworks QSX	LQSE-4T5-120-D	120	0-10v	Residential/ Commercial System	100.0	1.0		**99.4%**	**2.3%**
EL1-8.5-1000	**HI**							100.0	1.0		**100.0%**	**2.1%**
EL1-8.5-350	**WD/WD-2/WD-4**							100.0	1.0		**99.5%**	**1.1%**
EL1-8.5-1000	**HI-2**	Lutron	Nova T	NTSTV-DV-XX	120	0-10v	Wallbox	High & Low-End Trim Required			**99.9%**	**2.3%**
EL1-8.5-1000	**HI**										**99.8%**	**2.1%**
EL1-8.5-350	**WD/WD-2/WD-4**										**99.7%**	**1.1%**
EL1-01-8												
EL1-01-8-1000	**HI**	Crestron	iLux	CLS-EXP-DIMFLV	120	0-10v	Residential/ Commercial System	90.0	20.0		**100.0%**	**1.0%**
EL1-01-8-1000	**HI**	Crestron	Cameo	CLW-DIMFLVEX-P	120	0-10v	Wallbox/System	90.0	9.0		**100.0%**	**1.0%**
EL1-01-8-1000	**HI**	Crestron		CLX-2DIMFLV8	120	0-10v	Residential/ Commercial System	90.0	6.0		**100.0%**	**2.0%**
EL1-01-8-1000	**HI**	Crestron	Wireless Horizon	HZ-DIMUEX SERIES	120	0-10v	Wallbox/System	90.0	9.0		**100.0%**	**3.0%**
EL1-01-8-1000	**HI**	Crestron	Zum Wireless	ZUMMESH-5A-LV	120	0-10v	Wallbox/System	90.0	7.0		**100.0%**	**1.0%**
EL1-01-8-1000	**HI**	Crestron	Zum Wireless	ZUMMESH-JBOX	120	0-10v	Wallbox/System	90.0	7.0		**100.0%**	**2.0%**
EL1-01-8-1000	**HI**	Crestron	Zum Wireless	ZUMNETLINK-JBOX	120	0-10v	Wallbox/System	90.0	7.0		**100.0%**	**1.0%**
EL1-01-8-1000	**HI-2**	Lutron	Diva	DVST-XX	120	0-10v	Wallbox	High & Low-End Trim Required			**100.0%**	**0.1%**
EL1-01-8-1000	**HI**										**100.0%**	**0.1%**
EL1-01-8-350	**WD/WD-2/WD-4**										**100.0%**	**0.0%**
EL1-01-8-1400	**HI**										**100.0%**	**0.1%**
EL1-01-8-1000	**HI-2**	Lutron	Homeworks QSX	LQSE-4T5-120-D	120	0-10v	Residential/ Commercial System	90.0	3.0		**100.0%**	**0.2%**
EL1-01-8-1000	**HI**							90.0	3.0		**100.0%**	**0.1%**
EL1-01-8-350	**WD/WD-2/WD-4**							90.0	18.0		**100.0%**	**1.5%**
EL1-01-8-1400	**HI**							90.0	3.0		**100.0%**	**0.1%**
EL1-01-8-1000	**HI-2**	Lutron	Nova T	NTSTV-DV-XX	120	0-10v	Wallbox	High & Low-End Trim Required			**100.0%**	**0.1%**
EL1-01-8-1000	**HI**										**100.0%**	**0.1%**
EL1-01-8-350	**WD/WD-2/WD-4**										**100.0%**	**0.9%**
EL1-01-8-1400	**HI**										**100.0%**	**0.1%**
EL1-01-8-1000	**HI**	Vantage		LVOS-0-10-PWM	120	0-10v	Residential/ Commercial System	7.85 (VDC)	1.5 (VDC)	100	**94.9%**	**1.2%**
EL1-01-8-350	**WD/WD-2/WD-4**							8.0 (VDC)	1.6 (VDC)	100	**95.0%**	**3.0%**
EL1-01-8-1400	**HI**							7.8 (VDC)	1.5 (VDC)	100	**95.1%**	**0.5%**
EL1-01-8.5												
EL1-01-8.5-1000	**HI-2**	Lutron	Diva	DVST-XX	120	0-10v	Wallbox	High & Low-End Trim Required			**99.9%**	**0.1%**
EL1-01-8.5-1000	**HI**										**99.8%**	**0.1%**
EL1-01-8.5-350	**WD/WD-2/WD-4**										**100.0%**	**0.0%**
EL1-01-8.5-1000	**HI-2**	Lutron	Homeworks QSX	LQSE-4T5-120-D	120	0-10v	Residential/ Commercial System	100.0	1.0		**99.8%**	**0.1%**
EL1-01-8.5-1000	**HI**							100.0	1.0		**99.8%**	**0.1%**
EL1-01-8.5-350	**WD/WD-2/WD-4**							100.0	1.0		**98.6%**	**0.0%**
EL1-01-8.5-1000	**HI-2**	Lutron	Nova T	NTSTV-DV-XX	120	0-10v	Wallbox	High & Low-End Trim Required			**99.9%**	**0.1%**
EL1-01-8.5-1000	**HI**										**99.9%**	**0.1%**
EL1-01-8.5-350	**WD/WD-2/WD-4**										**99.8%**	**0.0%**

Dimmer compatibility testing performed using 120V/60Hz supply.
Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.
The design, specification, or performance of compatible dimmers is subject to change without notice.
0-10V dimming options are configured for linear control.
For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93801-01-2 - 04/2025

DIMMER COMPATIBILITY
800 SERIES
DRIVER MODELS: EL2-8, EL2-8.5, EL2-01-8, EL2-01-8.5
LED MODELS: HI, HI-2, WD/WD-2/WD-4

www.8lighting.com

No.8 Lighting Driver Model and Output	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Dimming Range	
								High-End (%)	Low-End (%)	High-End (%)	Low-End (%)
EL2-8											
EL2-8-1000*	**HI-2**	Lutron	Homeworks QSX	LQSE-1DAL2-D	120	DALI	Residential/ Commercial System	100.0	1.0	**100.0%**	**1.4%**
EL2-8-1000*	**HI**							100.0	1.0	**100.0%**	**1.3%**
EL2-8-350*	**WD/WD-2/WD-4**							100.0	1.0	**100.0%**	**0.6%**
EL2-8-1400*	**HI**							100.0	1.0	**100.0%**	**1.4%**
EL2-8-1000	**HI-2**	Vantage		DMX-DALI-GW	120	DALI	Residential/ Commercial System	100.0	1.0	**100.0%**	**1.4%**
EL2-8-1000	**HI**							100.0	1.0	**100.0%**	**1.3%**
EL2-8-350	**WD/WD-2/WD-4**							100.0	1.0	**100.0%**	**0.6%**
EL2-8-1400	**HI**							100.0	1.0	**100.0%**	**1.4%**
EL2-8.5											
EL2-8.5-1000*	**HI-2**	Lutron	Homeworks QSX	LQSE-1DAL2-D	120	DALI	Residential/ Commercial System	100.0	1.0	**100.0%**	**1.5%**
EL2-8.5-1000*	**HI**							100.0	1.0	**100.0%**	**1.4%**
EL2-8.5-350*	**WD/WD-2/WD-4**							100.0	1.0	**100.0%**	**0.6%**
EL2-01-8											
EL2-01-8-1000*	**HI-2**	Lutron	Homeworks QSX	LQSE-1DAL2-D	120	DALI	Residential/ Commercial System	100.0	1.0	**100.0%**	**0.5%**
EL2-01-8-1000*	**HI**							100.0	1.0	**100.0%**	**0.4%**
EL2-01-8-350*	**WD/WD-2/WD-4**							100.0	1.0	**100.0%**	**0.0%**
EL2-01-8-1400*	**HI**							100.0	1.0	**100.0%**	**0.5%**
EL2-01-8-1000	**HI-2**	Vantage		DMX-DALI-GW	120	DALI	Residential/ Commercial System	100.0	1.0	**100.0%**	**0.5%**
EL2-01-8-1000	**HI**							100.0	1.0	**100.0%**	**0.4%**
EL2-01-8-350	**WD/WD-2/WD-4**							100.0	1.0	**100.0%**	**0.0%**
EL2-01-8-1400	**HI**							100.0	1.0	**100.0%**	**0.5%**
EL2-01-8.5											
EL2-01-8.5-1000*	**HI-2**	Lutron	Homeworks QSX	LQSE-1DAL2-D	120	DALI	Residential/ Commercial System	100.0	1.0	**100.0%**	**0.1%**
EL2-01-8.5-1000*	**HI**							100.0	1.0	**100.0%**	**0.1%**
EL2-01-8.5-350*	**WD/WD-2/WD-4**							100.0	1.0	**100.0%**	**0.0%**

Dimmer compatibility testing performed using 120V/60Hz supply.
Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.
The design, specification, or performance of compatible dimmers is subject to change without notice.
***DALI Type 6: To minimize asynchronous behavior with Lutron LQSE-1DAL2-D module, limit the number of zones per DALI bus to a maximum of eight (8) per room.**
DALI dimming options are configured for logarithmic control.
For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93801-01-3 - 11/2026

DIMMER COMPATIBILITY
800 SERIES
DRIVER MODELS: EL3-8, EL4-8, EL5-8
LED MODEL: TW

www.8lighting.com

No.8 Lighting Driver Model and Output	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Dimming Range	
								High-End (%)	Low-End (%)	High-End (%)	Low-End (%)
EL3-8											
EL3-8-700*	**TW**	Lutron	Homeworks QSX	LQSE-1DAL2-D	120	DALI	Residential/ Commercial System	100.0	1.0	**100.0%**	**0.0%**
EL3-8-700	**TW**	Vantage		DMX-DALI-GW	120	DALI	Residential/ Commercial System	100.0	1.0	**100.0%**	**0.0%**
EL4-8											
EL4-8-700	**TW**	Lutron	Homeworks QSX	QSE-CI-DMX	120	DMX	Residential/ Commercial System	100.0	1.0	**99.8%**	**0.3%**
EL4-8-700	**TW**	Vantage		DMX-DALI-GW	120	DMX	Residential/ Commercial System	100.0	1.0	**99.8%**	**0.3%**
EL5-8											
EL5-8-700	**TW**	Lutron	Diva	DVST-XX	120	0-10v	Wallbox	High & Low-End Trim		**100.0%**	**0.1%**
EL5-8-700	**TW**	Lutron	Homeworks QSX	LQSE-4T5-120-D	120	0-10v	Residential/ Commercial System	90.0	10.0	**100.0%**	**0.1%**
EL5-8-700	**TW**	Lutron	Nova T	NTSTV-DV-XX	120	0-10v	Wallbox	High & Low-End Trim		**100.0%**	**0.1%**
EL5-8-700	**TW**	Vantage		LVOS-0-10-PWM	120	0-10v	Residential/ Commercial System	8.8 (VDC)	1.4 (VDC)	**100.0%**	**0.1%**

Dimmer compatibility testing performed using 120V/60Hz supply.
Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.
The design, specification, or performance of compatible dimmers is subject to change without notice.
***To minimize asynchronous behavior with Lutron LQSE-1DAL2-D module, limit the number of zones per DALI bus to a maximum of eight (8) per room.**
DALI dimming options are configured for logarithmic control. 0-10V and DMX dimming options are configured for linear control.
For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93801-01-4 - 04/2025

DIMMER COMPATIBILITY
800 SERIES
DRIVER MODELS: DAL2-8.5, DMX2-8.5, DIM6-8.5
LED MODEL: TW

www.8lighting.com

No.8 Lighting Driver Model and Output	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Dimming Range	
								High-End (%)	Low-End (%)	High-End (%)	Low-End (%)
DAL2-8.5 (Type 6)											
DAL2-8.5-700*	**TW**	Lutron	Homeworks QSX	LQSE-1DAL2-D	120	DALI	Residential/ Commercial System	100.0	1.0	**100.0%**	**0.1%**
DMX2-8.5											
DMX2-8.5-700	**TW**	Lutron	Homeworks QSX	QSE-CI-DMX	120	DMX	Residential/ Commercial System	N/A	N/A	**100.0%**	**0.9%**
DIM6-8.5											
DIM6-8.5-700	**TW**	Lutron	Homeworks QSX	LQSE-4T5-120-D	120	0-10v	Residential/ Commercial System	100.0	12.0	**100.0%**	**0.4%**

Dimmer compatibility testing performed using 120V/60Hz supply.
Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.
The design, specification, or performance of compatible dimmers is subject to change without notice.
***DALI Type 6: To minimize asynchronous behavior with Lutron LQSE-1DAL2-D module, limit the number of zones per DALI bus to a maximum of eight (8) per room.**
DALI dimming options are configured for logarithmic control. 0-10V and DMX dimming options are configured for linear control.
For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93801-01-5 -11/2026

DIMMER COMPATIBILITY
800 SERIES
DRIVER MODEL: DMX1-8/8.5
LED MODELS: HI, HI-2, WD/WD-2/WD-4

www.8lighting.com

No.8 Lighting Driver Model and Output	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Dimming Range	
								High-End (%)	Low-End (%)	High-End (%)	Low-End (%)
DMX1-8/8.5											
DMX1-8/8.5-1000	HI-2	Lutron	Homeworks QSX	QSE-CI-DMX	120	DMX	Residential/ Commercial System	N/A	N/A	100.0%	0.9%
DMX1-8/8.5-1000	HI									100.0%	0.8%
DMX1-8/8.5-350	WD/WD-2/WD-4									100.0%	0.5%

Dimmer compatibility testing performed using 120V/60Hz supply.
Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.
The design, specification, or performance of compatible dimmers is subject to change without notice.
DMX dimming options are configured for linear control.
For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93801-01-6 - 11/2026