DIMMER COMPATIBILITY
MPT3 SERIES
DRIVER MODELS: PR1-M, PR1-M-RT
LED MODELS: HI, HI-2, HI-3, WD/WD-2/WD-4

www.8lighting.com

No.8 Lighting Driver Model and Output	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Adjust (Vantage Only)	Dimming Range	
								High-End (%)	Low-End (%)		High-End (%)	Low-End (%)
PR1-M, PR1-M-RT												
PR1-M/M-RT-1000	HI	Lutron	Maestro	MA-PRO-XX	120	Forward Phase	Wallbox	High & Low-End Trim Required			100.0%	0.4%
PR1-M/M-RT-1400	HI										100.0%	4.4%
PR1-M/M-RT-1000	HI-2										100.0%	0.5%
PR1-M/M-RT-350	HI-3										98.7%	1.0%
PR1-M/M-RT-350	WD/WD-2/WD-4										98.3%	0.1%
PR1-M/M-RT-1000	HI	Lutron	Maestro	MA-PRO-XX	120	Reverse Phase	Wallbox	High & Low-End Trim Required			92.1%	0.5%
PR1-M/M-RT-1400	HI										100.0%	0.2%
PR1-M/M-RT-1000	HI-2										100.0%	0.5%
PR1-M/M-RT-350	HI-3										98.1%	0.2%
PR1-M/M-RT-350	WD/WD-2/WD-4										91.0%	0.1%
PR1-M/M-RT-1000	HI	Lutron	Maestro	MRF2-6ELV-120	120	Reverse Phase	Wallbox	High & Low-End Trim Required			100.0%	0.3%
PR1-M/M-RT-1400	HI										100.0%	0.1%
PR1-M/M-RT-1000	HI-2										100.0%	0.3%
PR1-M/M-RT-350	HI-3										97.1%	0.4%
PR1-M/M-RT-350	WD/WD-2/WD-4										90.0%	0.1%
PR1-M/M-RT-1000	HI	Lutron	Caseta	PD-5NE	120	Reverse Phase	Wallbox	High & Low-End Trim Required			99.9%	0.1%
PR1-M/M-RT-1400	HI										99.6%	0.1%
PR1-M/M-RT-1000	HI-2										99.9%	0.3%
PR1-M/M-RT-350	HI-3										93.2%	0.3%
PR1-M/M-RT-350	WD/WD-2/WD-4										100.0%	0.0%
PR1-M/M-RT-1000	HI	Lutron	Diva	DVCL-253PH	120	Forward Phase	Wallbox	High & Low-End Trim Required			100.0%	0.3%
PR1-M/M-RT-1400	HI										100.0%	0.4%
PR1-M/M-RT-1000	HI-2										100.0%	0.4%
PR1-M/M-RT-350	HI-3										99.6%	0.7%
PR1-M/M-RT-350	WD/WD-2/WD-4										98.4%	4.3%
PR1-M/M-RT-1000	HI	Lutron	Grafik Eye QS	QSGRJ-4P	120	Forward Phase	Residential/ Commercial System	80.0	5.0		100.0%	0.4%
PR1-M/M-RT-1400	HI							79.0	5.0		100.0%	0.6%
PR1-M/M-RT-1000	HI-2							79.0	1.0		100.0%	1.1%
PR1-M/M-RT-350	HI-3							100	3.0		98.7%	0.8%
PR1-M/M-RT-350	WD/WD-2/WD-4							100.0	8.0		99.3%	0.2%
PR1-M/M-RT-1000	HI	Lutron	Radio RA 2	RRD-PRO	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			100.0%	0.6%
PR1-M/M-RT-1400	HI										100.0%	4.1%
PR1-M/M-RT-1000	HI-2										100.0%	0.4%
PR1-M/M-RT-350	HI-3										99.0%	1.1%
PR1-M/M-RT-350	WD/WD-2/WD-4										98.4%	0.0%
PR1-M/M-RT-1000	HI	Lutron	Radio RA 2	RRD-PRO	120	Reverse Phase	Wallbox/System	High & Low-End Trim Required			100.0%	0.5%
PR1-M/M-RT-1400	HI										100.0%	0.4%
PR1-M/M-RT-1000	HI-2										100.0%	0.5%
PR1-M/M-RT-350	HI-3										98.7%	0.9%
PR1-M/M-RT-350	WD/WD-2/WD-4										88.8%	0.1%
PR1-M/M-RT-1000	HI	Lutron	Homeworks QS	HQRA-PRO	120	Forward Phase	Wallbox/System	High & Low-End Trim Required			100.0%	0.5%
PR1-M/M-RT-1400	HI										100.0%	0.8%
PR1-M/M-RT-1000	HI-2										100.0%	0.6%
PR1-M/M-RT-350	HI-3										99.2%	1.1%
PR1-M/M-RT-350	WD/WD-2/WD-4										98.3%	0.1%
PR1-M/M-RT-1000	HI	Lutron	Homeworks QS	HQRA-PRO	120	Reverse Phase	Wallbox/System	High & Low-End Trim Required			100.0%	0.4%
PR1-M/M-RT-1400	HI										100.0%	0.4%
PR1-M/M-RT-1000	HI-2										100.0%	0.6%
PR1-M/M-RT-350	HI-3										94.9%	0.2%
PR1-M/M-RT-350	WD/WD-2/WD-4										89.1%	0.1%
PR1-M/M-RT-1000	HI	Lutron	Homeworks QSX	LQSE-4A5-120-D	120	Forward Phase	Residential/ Commercial System	80.0	1.0		100.0%	0.6%
PR1-M/M-RT-1400	HI							80.0	1.0		100.0%	0.9%
PR1-M/M-RT-1000	HI-2							80.0	2.0		100.0%	0.7%
PR1-M/M-RT-350	HI-3							100.0	1.0		100.0%	1.0%
PR1-M/M-RT-350	WD/WD-2/WD-4							97.0	9.0		99.4%	0.1%
PR1-M/M-RT-1000	HI	Lutron	Homeworks QSX	LQSE-4A5-120-D	120	Reverse Phase	Residential/ Commercial System	84.0	6.0		100.0%	0.3%
PR1-M/M-RT-1400	HI							85.0	4.0		100.0%	0.2%
PR1-M/M-RT-1000	HI-2							84.0	5.0		100.0%	0.3%
PR1-M/M-RT-350	HI-3							100.0	10.0		99.9%	1.0%
PR1-M/M-RT-350	WD/WD-2/WD-4							100.0	38.0		100.0%	0.1%
PR1-M/M-RT-1000	HI	Crestron	Cameo Express Wireless	CLW-DIMEX-E	120	Forward Phase	Wallbox/System	75.0	3.0		100.0%	3.0%
PR1-M/M-RT-1400	HI							75.0	10.0		100.0%	7.0%
PR1-M/M-RT-350	WD/WD-2/WD-4							75.0	5.0		100.0%	1.0%
PR1-M/M-RT-1000	HI	Crestron	Cameo Wireless	CLW-DIMEX-P	120	Forward Phase	Wallbox/System	75.0	3.0		100.0%	3.0%
PR1-M/M-RT-1400	HI							75.0	10.0		100.0%	7.0%
PR1-M/M-RT-350	WD/WD-2/WD-4							75.0	5.0		100.0%	1.0%
PR1-M/M-RT-1000	HI	Crestron	Cameo Express Wireless	CLW-DIMSWEX-E	120	Forward Phase	Wallbox/System	75.0	3.0		100.0%	3.0%
PR1-M/M-RT-1400	HI							75.0	10.0		100.0%	7.0%
PR1-M/M-RT-350	WD/WD-2/WD-4							75.0	5.0		100.0%	1.0%
PR1-M/M-RT-1000	HI	Crestron	Cameo Wireless	CLW-DIMSWEX-P	120	Forward Phase	Wallbox/System	75.0	3.0		100.0%	3.0%
PR1-M/M-RT-1400	HI							75.0	10.0		100.0%	7.0%
PR1-M/M-RT-350	WD/WD-2/WD-4							75.0	5.0		100.0%	1.0%
PR1-M/M-RT-1000	HI	Crestron	Cameo Wireless	CLW-DIMUEX-P	120	Forward or Reverse Phase	Wallbox/System	80.0	3.0		100.0%	1.0%
PR1-M/M-RT-1400	HI							80.0	1.0		100.0%	1.0%
PR1-M/M-RT-350	WD/WD-2/WD-4							85.0	20.0		100.0%	1.0%
PR1-M/M-RT-1000	HI	Crestron		CLX-1DIMU4	120	Forward or Reverse Phase	Residential/ Commercial System	80.0	5.0		100.0%	1.0%
PR1-M/M-RT-1400	HI							80.0	25.0		100.0%	5.0%
PR1-M/M-RT-350	WD/WD-2/WD-4							85.0	20.0		100.0%	1.0%
PR1-M/M-RT-1000	HI	Crestron		CLX-2DIMU8	120	Forward or Reverse Phase	Residential/ Commercial System	80.0	5.0		100.0%	1.0%
PR1-M/M-RT-1400	HI							80.0	25.0		100.0%	5.0%
PR1-M/M-RT-350	WD/WD-2/WD-4							85.0	20.0		100.0%	1.0%
PR1-M/M-RT-1000	HI	Crestron	Wireless Horizon	HZ-DIMEX SERIES	120	Forward Phase	Wallbox/System	80.0	10.0		100.0%	1.0%
PR1-M/M-RT-1400	HI							80.0	3.0		100.0%	1.0%
PR1-M/M-RT-350	WD/WD-2/WD-4							85.0	15.0		100.0%	1.0%
PR1-M/M-RT-1000	HI	Crestron	Wireless Horizon	HZ-DIMUEX SERIES	120	Forward or Reverse Phase	Wallbox/System	80.0	10.0		100.0%	2.0%
PR1-M/M-RT-1400	HI							80.0	3.0		100.0%	1.0%
PR1-M/M-RT-350	WD/WD-2/WD-4							85.0	15.0		100.0%	1.0%

No.8 Lighting Driver Model and Output	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Adjust (Vantage Only)	Dimming Range	
								High-End (%)	Low-End (%)		High-End (%)	Low-End (%)
PR1-M, PR1-M-RT (Continued)												
PR1-M/M-RT-1000	**HI**	Crestron		P-DIMEX	120	Forward Phase	Wallbox/System	75.0	3.0		**100.0%**	**3.0%**
PR1-M/M-RT-1400	**HI**							75.0	10.0		**100.0%**	**7.0%**
PR1-M/M-RT-350	**WD/WD-2/WD-4**							75.0	5.0		**100.0%**	**1.0%**
PR1-M/M-RT-1000	**HI**	Crestron	Zum Wireless	ZUMMESH-DELV	120	Reverse Phase	Wallbox/System	80.0	10.0		**100.0%**	**1.0%**
PR1-M/M-RT-1400	**HI**							85.0	9.0		**100.0%**	**1.0%**
PR1-M/M-RT-350	**WD/WD-2/WD-4**							80.0	25.0		**100.0%**	**1.0%**
PR1-M/M-RT-1000	**HI**	Crestron	Zum Wireless	ZUMMESH-DIM	120	Forward Phase	Wallbox/System	80.0	20.0		**100.0%**	**8.0%**
PR1-M/M-RT-1400	**HI**							80.0	15.0		**100.0%**	**5.0%**
PR1-M/M-RT-350	**WD/WD-2/WD-4**							80.0	25.0		**100.0%**	**2.0%**
PR1-M/M-RT-1000	**HI**	Crestron	Zum Wireless	ZUMMESH-EXP-16A-DIMU	120	Forward or Reverse Phase	Wallbox/System	80.0	15.0		**100.0%**	**3.0%**
PR1-M/M-RT-1400	**HI**							80.0	14.0		**100.0%**	**1.0%**
PR1-M/M-RT-350	**WD/WD-2/WD-4**							85.0	20.0		**100.0%**	**1.0%**
PR1-M/M-RT-1000	**HI**	Vantage		ScenePoint	120	Forward Phase	Residential System	78.5	3.5	85	**94.9%**	**1.9%**
PR1-M/M-RT-1400	**HI**							73.5	4.0	95	**95.1%**	**1.8%**
PR1-M/M-RT-350	**WD/WD-2/WD-4**							81.0	9.0	100	**95.0%**	**1.5%**
PR1-M/M-RT-1000	**HI**	Vantage		SDM12-EM	120	Forward Phase	Residential System	75.4	2.0	85	**95.3%**	**1.2%**
PR1-M/M-RT-1400	**HI**							68.0	2.5	95	**94.9%**	**2.4%**
PR1-M/M-RT-350	**WD/WD-2/WD-4**							77.5	7.0	100	**95.0%**	**1.2%**
PR1-M/M-RT-1000	**HI**	Vantage		UDM-FWD	120	Forward Phase	Residential System	78.2	3.0	85	**94.9%**	**1.5%**
PR1-M/M-RT-350	**WD/WD-2/WD-4**							79.5	7.0	100	**95.0%**	**0.9%**
PR1-M/M-RT-1400	**HI**							72.0	3.5	100	**94.9%**	**2.3%**
PR1-M/M-RT-1000	**HI**	Vantage		UDM-REV	120	Reverse Phase	Residential System	84.5	6.5	40	**95.4%**	**1.6%**
PR1-M/M-RT-350	**WD/WD-2/WD-4**							87.5	22.0	25	**95.3%**	**1.6%**
PR1-M/M-RT-1400	**HI**							80.4	6.8	40	**95.1%**	**2.2%**
PR1-M/M-RT-1000	**HI**	Vantage		UDS-F	120	Forward Phase	Wallbox/System	81.0	3.5	85	**95.0%**	**1.5%**
PR1-M/M-RT-350	**WD/WD-2/WD-4**							82.4	9.0	100	**94.6%**	**1.0%**
PR1-M/M-RT-1400	**HI**							75.5	4.0	90	**95.1%**	**1.4%**
PR1-M/M-RT-1000	**HI**	Vantage		UDS-R	120	Reverse Phase	Wallbox/System	82.4	4.5	40	**94.8%**	**1.2%**
PR1-M/M-RT-350	**WD/WD-2/WD-4**							86.0	21.0	25	**94.8%**	**2.3%**
PR1-M/M-RT-1400	**HI**							79.2	4.7	40	**95.0%**	**2.5%**

Dimmer compatibility testing performed using 120V/60Hz supply.
Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.
The design, specification, or performance of compatible dimmers is subject to change without notice.
For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93803-01-1 - 04/2026

DIMMER COMPATIBILITY
MPT3 SERIES
DRIVER MODELS: PR1-M2/M4
LED MODELS: HI, HI-2, HI-3, WD/WD-2/WD-4

www.8lighting.com

No.8 Lighting Driver Model and Output	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Dimming Range	
								High-End (%)	Low-End (%)	High-End (%)	Low-End (%)
PR1-M2/M4											
PR1-M2/M4-1000	HI	Lutron	Maestro	MA-PRO-XX	120	Forward Phase	Wallbox	High & Low-End Trim Required		100.0%	0.8%
PR1-M2/M4-1000	HI-2									100.0%	1.5%
PR1-M2/M4-350	HI-3									99.2%	1.2%
PR1-M2/M4-350	WD/WD-2/WD-4									100.0%	0.7%
PR1-M2/M4-1000	HI	Lutron	Maestro	MA-PRO-XX	120	Reverse Phase	Wallbox	High & Low-End Trim Required		100.0%	0.4%
PR1-M2/M4-1000	HI-2									100.0%	0.7%
PR1-M2/M4-350	HI-3									97.4%	0.7%
PR1-M2/M4-350	WD/WD-2/WD-4									100.0%	0.2%
PR1-M2/M4-1000	HI	Lutron	Maestro	MRF2-6ELV-120	120	Reverse Phase	Wallbox	High & Low-End Trim Required		100.0%	0.2%
PR1-M2/M4-1000	HI-2									100.0%	0.3%
PR1-M2/M4-350	HI-3									100.0%	0.7%
PR1-M2/M4-350	WD/WD-2/WD-4									100.0%	0.3%
PR1-M2/M4-1000	HI	Lutron	Caseta	PD-5NE	120	Reverse Phase	Wallbox	High & Low-End Trim Required		100.0%	0.7%
PR1-M2/M4-1000	HI-2									98.7%	0.8%
PR1-M2/M4-350	HI-3									100.0%	0.6%
PR1-M2/M4-350	WD/WD-2/WD-4									100.0%	0.3%
PR1-M2/M4-1000	HI	Lutron	Diva	DVRF-5NE	120	Reverse Phase	Wallbox	High & Low-End Trim Required		100.0%	0.8%
PR1-M2/M4-1000	HI-2									97.7%	0.5%
PR1-M2/M4-350	HI-3									99.9%	0.5%
PR1-M2/M4-350	WD/WD-2/WD-4									100.0%	0.2%
PR1-M2/M4-1000	HI	Lutron	Radio RA 2	RRD-PRO	120	Forward Phase	Wallbox/System	High & Low-End Trim Required		100.0%	1.1%
PR1-M2/M4-1000	HI-2									97.2%	1.0%
PR1-M2/M4-350	HI-3									99.4%	0.9%
PR1-M2/M4-350	WD/WD-2/WD-4									100.0%	0.5%
PR1-M2/M4-1000	HI	Lutron	Radio RA 2	RRD-PRO	120	Reverse Phase	Wallbox/System	High & Low-End Trim Required		100.0%	0.4%
PR1-M2/M4-1000	HI-2									97.6%	0.6%
PR1-M2/M4-350	HI-3									99.5%	0.6%
PR1-M2/M4-350	WD/WD-2/WD-4									99.2%	0.4%
PR1-M2/M4-1000	HI	Lutron	Homeworks QS	HQRA-PRO	120	Forward Phase	Wallbox/System	High & Low-End Trim Required		100.0%	1.1%
PR1-M2/M4-1000	HI-2									97.1%	1.1%
PR1-M2/M4-350	HI-3									99.2%	0.7%
PR1-M2/M4-350	WD/WD-2/WD-4									99.8%	0.5%
PR1-M2/M4-1000	HI	Lutron	Homeworks QS	HQRA-PRO	120	Reverse Phase	Wallbox/System	High & Low-End Trim Required		100.0%	0.4%
PR1-M2/M4-1000	HI-2									97.4%	0.3%
PR1-M2/M4-350	HI-3									99.2%	0.6%
PR1-M2/M4-350	WD/WD-2/WD-4									100.0%	0.3%
PR1-M2/M4-1000	HI	Lutron	Homeworks QSX	LQSE-4A5-120-D	120	Forward Phase	Residential/ Commercial System	100.0	2.0	100.0%	0.9%
PR1-M2/M4-1000	HI-2							100.0	2.0	100.0%	1.1%
PR1-M2/M4-350	HI-3							100.0	2.0	99.2%	0.6%
PR1-M2/M4-350	WD/WD-2/WD-4							100.0	2.0	99.5%	0.4%
PR1-M2/M4-1000	HI	Lutron	Homeworks QSX	LQSE-4A5-120-D	120	Reverse Phase	Residential/ Commercial System	100.0	5.0	100.0%	0.2%
PR1-M2/M4-1000	HI-2							100.0	5.0	100.0%	0.3%
PR1-M2/M4-350	HI-3							100.0	15.0	100.0%	1.0%
PR1-M2/M4-350	WD/WD-2/WD-4							100.0	10.0	100.0%	0.3%

Dimmer compatibility testing performed using 120V/60Hz supply.
Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.
The design, specification, or performance of compatible dimmers is subject to change without notice.
For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93803-01-2 - 04/2026

DIMMER COMPATIBILITY
MPT3 SERIES
DRIVER MODELS: EL1-M-RT-1L, EL1-01-M-RT-1L
LED MODELS: HI, HI-2, WD/WD-2/WD-4

www.8lighting.com

No.8 Lighting Driver Model and Output	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Adjust (Vantage Only)	Dimming Range	
								High-End (%)	Low-End (%)		High-End (%)	Low-End (%)
EL1-M-RT-1L												
EL1-M-RT-1L-1000	**HI**	Lutron	Diva	DVST-XX	120	0-10v	Wallbox	High & Low-End Trim Required			**100.0%**	**2.0%**
EL1-M-RT-1L-1400	**HI**										**100.0%**	**2.3%**
EL1-M-RT-1L-1000	**HI-2**										**100.0%**	**2.3%**
EL1-M-RT-1L-350	**WD/WD-2/WD-4**										**100.0%**	**0.9%**
EL1-M-RT-1L-1000	**HI**	Lutron	Homeworks QSX	LQSE-4T5-120-D	120	0-10v	Residential/ Commercial System	90.0	2.0		**100.0%**	**2.0%**
EL1-M-RT-1L-1400	**HI**							90.0	2.0		**100.0%**	**2.2%**
EL1-M-RT-1L-1000	**HI-2**							90.0	3.0		**100.0%**	**2.3%**
EL1-M-RT-1L-350	**WD/WD-2/WD-4**							90.0	3.0		**100.0%**	**0.9%**
EL1-M-RT-1L-1000	**HI**	Lutron	Nova T	NTSTV-DV-XX	120	0-10v	Wallbox	High & Low-End Trim Required			**100.0%**	**2.0%**
EL1-M-RT-1L-1400	**HI**										**100.0%**	**2.2%**
EL1-M-RT-1L-1000	**HI-2**										**100.0%**	**2.3%**
EL1-M-RT-1L-350	**WD/WD-2/WD-4**										**100.0%**	**0.9%**
EL1-M-RT-1L-1000	**HI**	Vantage		LVOS-0-10-PWM	120	0-10v	Residential/ Commercial System	7.8 (VDC)	1.4 (VDC)	100	**95.0%**	**2.1%**
EL1-M-RT-1L-1400	**HI**							7.8 (VDC)	1.5 (VDC)	100	**94.7%**	**3.7%**
EL1-M-RT-1L-1000	**HI-2**							8.0 (VDC)	1.4 (VDC)	100	**94.8%**	**1.6%**
EL1-M-RT-1L-350	**WD/WD-2/WD-4**							8.1 (VDC)	1.5 (VDC)	100	**95.2%**	**2.1%**
EL1-01-M-RT-1L												
EL1-01-M-RT-1L-1000	**HI**	Lutron	Diva	DVST-XX	120	0-10v	Wallbox	High & Low-End Trim Required			**100.0%**	**0.1%**
EL1-01-M-RT-1L-1400	**HI**										**100.0%**	**0.1%**
EL1-01-M-RT-1L-1000	**HI-2**										**100.0%**	**0.1%**
EL1-01-M-RT-1L-350	**WD/WD-2/WD-4**										**100.0%**	**0.0%**
EL1-01-M-RT-1L-1000	**HI**	Lutron	Homeworks QSX	LQSE-4T5-120-D	120	0-10v	Residential/ Commercial System	90.0	3.0		**100.0%**	**0.1%**
EL1-01-M-RT-1L-1400	**HI**							90.0	3.0		**100.0%**	**0.1%**
EL1-01-M-RT-1L-1000	**HI-2**							90.0	3.0		**100.0%**	**0.2%**
EL1-01-M-RT-1L-350	**WD/WD-2/WD-4**							90.0	18.0		**100.0%**	**1.5%**
EL1-01-M-RT-1L-1000	**HI**	Lutron	Nova T	NTSTV-DV-XX	120	0-10v	Wallbox	High & Low-End Trim Required			**100.0%**	**0.1%**
EL1-01-M-RT-1L-1400	**HI**										**100.0%**	**0.1%**
EL1-01-M-RT-1L-1000	**HI-2**										**100.0%**	**0.1%**
EL1-01-M-RT-1L-350	**WD/WD-2/WD-4**										**100.0%**	**0.9%**
EL1-01-M-RT-1L-1000	**HI**	Vantage		LVOS-0-10-PWM	120	0-10v	Residential/ Commercial System	7.9 (VDC)	1.5 (VDC)	100	**94.9%**	**1.2%**
EL1-01-M-RT-1L-1400	**HI**							7.8 (VDC)	1.5 (VDC)	100	**95.1%**	**0.5%**
EL1-01-M-RT-1L-1000	**HI-2**							8.0 (VDC)	1.5 (VDC)	100	**94.8%**	**1.4%**
EL1-01-M-RT-1L-350	**WD/WD-2/WD-4**							8.0 (VCD)	1.6 (VCD)	100	**95.0%**	**3.0%**

Dimmer compatibility testing performed using 120V/60Hz supply.
Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.
The design, specification, or performance of compatible dimmers is subject to change without notice.
0-10V dimming options are configured for linear control.
For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93803-01-3 - 04/2026

DIMMER COMPATIBILITY
MPT3 SERIES
DRIVER MODELS: EL2-M-RT-1L, EL2-01-M-RT-1L
LED MODELS: HI, HI-2, WD/WD-2/WD-4

www.8lighting.com

No.8 Lighting Driver Model and Output	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Dimming Range	
								High-End (%)	Low-End (%)	High-End (%)	Low-End (%)
EL2-M-RT-1L											
EL2-M-RT-1L-1000*	**HI**	Lutron	Homeworks QSX	LQSE-1DAL2-D	120	DALI-2 Type 6	Residential/ Commercial System	100.0	1.0	**100.0%**	**1.3%**
EL2-M-RT-1L-1400*	**HI**							100.0	1.0	**100.0%**	**1.4%**
EL2-M-RT-1L-1000*	**HI-2**							100.0	1.0	**100.0%**	**1.4%**
EL2-M-RT-1L-350*	**WD/WD-2/WD-4**							100.0	1.0	**100.0%**	**0.6%**
EL2-M-RT-1L-1000	**HI**	Vantage		DMX-DALI-GW	120	DALI-2 Type 6	Residential/ Commercial System	100.0	1.0	**100.0%**	**1.3%**
EL2-M-RT-1L-1400	**HI**							100.0	1.0	**100.0%**	**1.4%**
EL2-M-RT-1L-1000	**HI-2**							100.0	1.0	**100.0%**	**1.4%**
EL2-M-RT-1L-350	**WD/WD-2/WD-4**							100.0	1.0	**100.0%**	**0.6%**
EL2-01-M-RT-1L											
EL2-01-M-RT-1L-1000*	**HI**	Lutron	Homeworks QSX	LQSE-1DAL2-D	120	DALI-2 Type 6	Residential/ Commercial System	100.0	1.0	**100.0%**	**0.4%**
EL2-01-M-RT-1L-1400*	**HI**							100.0	1.0	**100.0%**	**0.5%**
EL2-01-M-RT-1L-1000*	**HI-2**							100.0	1.0	**100.0%**	**0.5%**
EL2-01-M-RT-1L-350*	**WD/WD-2/WD-4**							100.0	1.0	**100.0%**	**0.0%**
EL2-01-M-RT-1L-1000	**HI**	Vantage		DMX-DALI-GW	120	DALI-2 Type 6	Residential/ Commercial System	100.0	1.0	**100.0%**	**0.4%**
EL2-01-M-RT-1L-1400	**HI**							100.0	1.0	**100.0%**	**0.5%**
EL2-01-M-RT-1L-1000	**HI-2**							100.0	1.0	**100.0%**	**0.5%**
EL2-01-M-RT-1L-350	**WD/WD-2/WD-4**							100.0	1.0	**100.0%**	**0.0%**

Dimmer compatibility testing performed using 120V/60Hz supply.
Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.
The design, specification, or performance of compatible dimmers is subject to change without notice.
***To minimize asynchronous behavior with Lutron LQSE-1DAL2-D module, limit the number of zones per DALI bus to a maximum of eight (8) per room.**
are configured for logarithmic
For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93803-01-4 - 04/2026

DIMMER COMPATIBILITY
MPT3 SERIES
DRIVER MODELS: EL3-M-RT-1L, EL4-M-RT-1L, EL5-M-RT-1L
LED MODEL: TW

www.8lighting.com

No.8 Lighting Driver Model and Output	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Dimming Range	
								High-End (%)	Low-End (%)	High-End (%)	Low-End (%)
EL3-8											
EL3-M-RT-1L-700*	**TW**	Lutron	Homeworks QSX	LQSE-1DAL2-D	120	DALI-2 Type 6	Residential/ Commercial System	100.0	1.0	**100.0%**	**0.0%**
EL3-M-RT-1L-700	**TW**	Vantage		DMX-DALI-GW	120	DALI-2 Type 6	Residential/ Commercial System	100.0	1.0	**100.0%**	**0.0%**
EL4-8											
EL4-M-RT-1L-700	**TW**	Lutron	Homeworks QSX	QSE-CI-DMX	120	DMX	Residential/ Commercial System	100.0	1.0	**99.8%**	**0.3%**
EL4-M-RT-1L-700	**TW**	Vantage		DMX-DALI-GW	120	DMX	Residential/ Commercial System	100.0	1.0	**99.8%**	**0.3%**
EL5-8											
EL5-M-RT-1L-700	**TW**	Lutron	Diva	DVST-XX	120	0-10v	Wallbox	High & Low-End Trim		**100.0%**	**0.1%**
EL5-M-RT-1L-700	**TW**	Lutron	Homeworks QSX	LQSE-4T5-120-D	120	0-10v	Residential/ Commercial System	90.0	10.0	**100.0%**	**0.1%**
EL5-M-RT-1L-700	**TW**	Lutron	Nova T	NTSTV-DV-XX	120	0-10v	Wallbox	High & Low-End Trim		**100.0%**	**0.1%**
EL5-M-RT-1L-700	**TW**	Vantage		LVOS-0-10-PWM	120	0-10v	Residential/ Commercial System	8.8 (VDC)	1.4 (VDC)	**100.0%**	**0.1%**

Dimmer compatibility testing performed using 120V/60Hz supply.
Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.
The design, specification, or performance of compatible dimmers is subject to change without notice.
***To minimize asynchronous behavior with Lutron LQSE-1DAL2-D module, limit the number of zones per DALI bus to a maximum of eight (8) per room.**
DALI-2 Type 6 dimming options are configured for logarithmic control. 0-10V and DMX dimming options are configured for linear control.
For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93803-01-5 - 04/2026

DIMMER COMPATIBILITY
MPT3 SERIES
DRIVER MODELS: DAL2-M-RT-1L, DMX2-M-RT-1L, DIM6-M-RT-1L
LED MODEL: TW

www.8lighting.com

No.8 Lighting Driver Model and Output	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Dimming Range	
								High-End (%)	Low-End (%)	High-End (%)	Low-End (%)
DAL2-M-RT-1L (Type 6)											
DAL2-M-RT-1L-700*	**TW**	Lutron	Homeworks QSX	LQSE-1DAL2-D	120	DALI	Residential/ Commercial System	100.0	1.0	**100.0%**	**0.1%**
DMX2-M-RT-1L											
DMX2-M-RT-1L-700	**TW**	Lutron	Homeworks QSX	QSE-CI-DMX	120	DMX	Residential/ Commercial System	N/A	N/A	**100.0%**	**0.9%**
DIM6-M-RT-1L											
DIM6-M-RT-1L-700	**TW**	Lutron	Homeworks QSX	LQSE-4T5-120-D	120	0-10v	Residential/ Commercial System	100.0	12.0	**100.0%**	**0.4%**

Dimmer compatibility testing performed using 120V/60Hz supply.
Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.
The design, specification, or performance of compatible dimmers is subject to change without notice.
***DALI Type 6: To minimize asynchronous behavior with Lutron LQSE-1DAL2-D module, limit the number of zones per DALI bus to a maximum of eight (8) per room.**
DALI dimming options are configured for logarithmic control. 0-10V and DMX dimming options are configured for linear control.
For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93803-01-6 -11/2026

DIMMER COMPATIBILITY
MPT3 SERIES
DRIVER MODEL: DMX1-M-RT-1L
LED MODELS: HI, HI-2, WD/WD-2/WD-4

www.8lighting.com

No.8 Lighting Driver Model and Output	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Dimming Range	
								High-End (%)	Low-End (%)	High-End (%)	Low-End (%)
DMX1-M-RT-1L											
DMX1-M-RT-1L-1000	HI-2	Lutron	Homeworks QSX	QSE-CI-DMX	120	DMX	Residential/ Commercial System	N/A	N/A	100.0%	0.9%
DMX1-M-RT-1L-1000	HI									100.0%	0.8%
DMX1-M-RT-1L-350	WD/WD-2/WD-4									100.0%	0.5%

Dimmer compatibility testing performed using 120V/60Hz supply.
Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.
The design, specification, or performance of compatible dimmers is subject to change without notice.
DMX dimming options are configured for linear control.
For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93803-01-7 - 11/2026