DIMMER COMPATIBILITY
200 SERIES
DRIVER MODEL: PR1-2, PR1-2-R
LED MODELS: HI-27/30/35/40, WD-5/6/7

www.8lighting.com

No.8 Lighting Driver Model	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Dimming Range	
								High-End (%)	Low-End (%)	High-End (%)	Low-End (%)
PR1-2, PR1-2-R											
PR1-2/2-R	**HI-27/30/35/40**	Lutron	Maestro	MA-PRO-XX	120	Forward Phase	Wallbox	High & Low-End Trim Required		**100.0%**	**0.7%**
PR1-2/2-R	**WD-5/6/7**									**100.0%**	**0.5%**
PR1-2/2-R	**HI-27/30/35/40**	Lutron	Maestro	MA-PRO-XX	120	Reverse Phase	Wallbox	High & Low-End Trim Required		**100.0%**	**0.6%**
PR1-2/2-R	**WD-5/6/7**									**100.0%**	**0.5%**
PR1-2/2-R	**HI-27/30/35/40**	Lutron	Maestro	MRF2-6ELV-120	120	Reverse Phase	Wallbox	High & Low-End Trim Required		**100.0%**	**0.7%**
PR1-2/2-R	**WD-5/6/7**									**100.0%**	**0.5%**
PR1-2/2-R	**HI-27/30/35/40**	Lutron	Caseta	PD-5NE	120	Reverse Phase	Wallbox	High & Low-End Trim Required		**100.0%**	**0.5%**
PR1-2/2-R	**WD-5/6/7**									**100.0%**	**0.6%**
PR1-2/2-R	**HI-27/30/35/40**	Lutron	Diva	DVRF-5NE	120	Reverse Phase	Wallbox	High & Low-End Trim Required		**100.0%**	**0.6%**
PR1-2/2-R	**WD-5/6/7**									**100.0%**	**0.5%**
PR1-2/2-R	**HI-27/30/35/40**	Lutron	Grafik Eye QS	QSGRJ-4P	120	Forward Phase	Residential/ Commercial System	90.0	10.0	**100.0%**	**1.7%**
PR1-2/2-R	**WD-5/6/7**							90.0	10.0	**100.0%**	**0.5%**
PR1-2/2-R	**HI-27/30/35/40**	Lutron	Radio RA 2	RRD-PRO	120	Forward Phase	Wallbox/System	High & Low-End Trim Required		**100.0%**	**0.9%**
PR1-2/2-R	**WD-5/6/7**									**100.0%**	**0.7%**
PR1-2/2-R	**HI-27/30/35/40**	Lutron	Radio RA 2	RRD-PRO	120	Reverse Phase	Wallbox/System	High & Low-End Trim Required		**100.0%**	**0.5%**
PR1-2/2-R	**WD-5/6/7**									**100.0%**	**0.5%**
PR1-2/2-R	**HI-27/30/35/40**	Lutron	Homeworks QS	HQRA-PRO	120	Forward Phase	Wallbox/System	High & Low-End Trim Required		**100.0%**	**1.2%**
PR1-2/2-R	**WD-5/6/7**									**100.0%**	**0.8%**
PR1-2/2-R	**HI-27/30/35/40**	Lutron	Homeworks QS	HQRA-PRO	120	Reverse Phase	Wallbox/System	High & Low-End Trim Required		**100.0%**	**0.6%**
PR1-2/2-R	**WD-5/6/7**									**100.0%**	**0.8%**
PR1-2/2-R	**HI-27/30/35/40**	Lutron	Homeworks QSX	LQSE-4A5-120-D	120	Forward Phase	Residential/ Commercial System	100.0	4.0	**100.0%**	**1.0%**
PR1-2/2-R	**WD-5/6/7**							100.0	2.0	**100.0%**	**0.6%**
PR1-2/2-R	**HI-27/30/35/40**	Lutron	Homeworks QSX	LQSE-4A5-120-D	120	Reverse Phase	Residential/ Commercial System	100.0	15.0	**100.0%**	**1.2%**
PR1-2/2-R	**WD-5/6/7**							100.0	10.0	**100.0%**	**0.5%**

Dimmer compatibility testing performed using 120V/60Hz supply.
Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.
The design, specification, or performance of compatible dimmers is subject to change without notice.
For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93804-01-1 - 11/2026

DIMMER COMPATIBILITY
200 SERIES
DRIVER MODEL: DIM3-2, DIM3-2-R
LED MODELS: HI-27/30/35/40, WD-5/6/7

www.8lighting.com

No.8 Lighting Driver Model	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Dimming Range	
								High-End (%)	Low-End (%)	High-End (%)	Low-End (%)
DIM3-2, DIM3-2-R											
DIM3-2/2-R	HI-27/30/35/40	Lutron	Maestro	MA-PRO-XX	120	Forward Phase	Wallbox	High & Low-End Trim Required		100.0%	2.2%
DIM3-2/2-R	WD-5/6/7									100.0%	1.8%
DIM3-2/2-R	HI-27/30/35/40	Lutron	Maestro	MA-PRO-XX	120	Reverse Phase	Wallbox	High & Low-End Trim Required		100.0%	2.0%
DIM3-2/2-R	WD-5/6/7									100.0%	0.9%
DIM3-2/2-R	HI-27/30/35/40	Lutron	Maestro	MRF2-6ELV-120	120	Reverse Phase	Wallbox	High & Low-End Trim Required		100.0%	2.4%
DIM3-2/2-R	WD-5/6/7									100.0%	1.7%
DIM3-2/2-R	HI-27/30/35/40	Lutron	Diva	DVRF-5NE	120	Reverse Phase	Wallbox	High & Low-End Trim Required		100.0%	13.8%
DIM3-2/2-R	WD-5/6/7									100.0%	1.8%
DIM3-2/2-R	HI-27/30/35/40	Lutron	Grafik Eye QS	QSGRJ-4P	120	Forward Phase	Residential/ Commercial System	90.0	10.0	100.0%	10.9%
DIM3-2/2-R	WD-5/6/7							90.0	12.0	100.0%	4.8%
DIM3-2/2-R	HI-27/30/35/40	Lutron	Radio RA 2	RRD-PRO	120	Forward Phase	Wallbox/System	High & Low-End Trim Required		100.0%	3.2%
DIM3-2/2-R	WD-5/6/7									100.0%	1.8%
DIM3-2/2-R	HI-27/30/35/40	Lutron	Radio RA 2	RRD-PRO	120	Reverse Phase	Wallbox/System	High & Low-End Trim Required		100.0%	1.5%
DIM3-2/2-R	WD-5/6/7									100.0%	0.9%
DIM3-2/2-R	HI-27/30/35/40	Lutron	Homeworks QS	HQRA-PRO	120	Forward Phase	Wallbox/System	High & Low-End Trim Required		100.0%	3.3%
DIM3-2/2-R	WD-5/6/7									100.0%	2.2%
DIM3-2/2-R	HI-27/30/35/40	Lutron	Homeworks QS	HQRA-PRO	120	Reverse Phase	Wallbox/System	High & Low-End Trim Required		100.0%	3.4%
DIM3-2/2-R	WD-5/6/7									100.0%	0.9%
DIM3-2/2-R	HI-27/30/35/40	Lutron	Homeworks QSX	LQSE-4A5-120-D	120	Forward Phase	Residential/ Commercial System	100.0	3.0	100.0%	3.2%
DIM3-2/2-R	WD-5/6/7							100.0	2.0	100.0%	1.8%
DIM3-2/2-R	HI-27/30/35/40	Lutron	Homeworks QSX	LQSE-4A5-120-D	120	Reverse Phase	Residential/ Commercial System	100.0	6.0	100.0%	4.7%
DIM3-2/2-R	WD-5/6/7							100.0	10.0	100.0%	1.5%

Dimmer compatibility testing performed using 120V/60Hz supply.
Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.
The design, specification, or performance of compatible dimmers is subject to change without notice.
For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93804-01-2 - 11/2026

DIMMER COMPATIBILITY
200 SERIES
DRIVER MODELS: DIM4-2, DIM4-2-R, EL1-2, EL1-2-R, EL1-01-2, EL1-01-2-R
LED MODELS: HI-27/30/35/40, WD-5/6/7

www.8lighting.com

No.8 Lighting Driver Model	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Dimming Range	
								High-End (%)	Low-End (%)	High-End (%)	Low-End (%)
DIM4-2, DIM4-2-R											
DIM4-2/2-R	HI-27/30/35/40	Lutron	Homeworks QSX	LQSE-4T5-120-D	120	0-10v	Residential/ Commercial System	100.0	1.0	100.0%	5.6%
DIM4-2/2-R	WD-5/6/7							100.0	1.0	100.0%	3.3%
DIM4-2/2-R	HI-27/30/35/40	Lutron	Diva	DVSTV-XX	120	0-10v	Wallbox	High & Low-End Trim Required		100.0%	6.8%
DIM4-2/2-R	WD-5/6/7									100.0%	4.0%
DIM4-2/2-R	HI-27/30/35/40	Lutron	Nova T	NTSTV-DV-XX	120	0-10v	Wallbox	High & Low-End Trim Required		100.0%	7.9%
DIM4-2/2-R	WD-5/6/7									100.0%	4.2%
EL1-2, EL1-2-R											
EL1-2/2-R	HI-27/30/35/40	Lutron	Homeworks QSX	LQSE-4T5-120-D	120	0-10v	Residential/ Commercial System	100.0	2.0	100.0%	1.4%
EL1-2/2-R	WD-5/6/7							100.0	1.0	100.0%	0.9%
EL1-2/2-R	HI-27/30/35/40	Lutron	Diva	DVSTV-XX	120	0-10v	Wallbox	High & Low-End Trim Required		100.0%	1.6%
EL1-2/2-R	WD-5/6/7									100.0%	0.9%
EL1-2/2-R	HI-27/30/35/40	Lutron	Nova T	NTSTV-DV-XX	120	0-10v	Wallbox	High & Low-End Trim Required		100.0%	1.4%
EL1-2/2-R	WD-5/6/7									100.0%	1.0%
EL1-01-2, EL1-01-2-R											
EL1-01-2/2-R	HI-27/30/35/40	Lutron	Homeworks QSX	LQSE-4T5-120-D	120	0-10v	Residential/ Commercial System	100.0	17.0	100.0%	0.9%
EL1-01-2/2-R	WD-5/6/7							100.0	17.0	100.0%	0.6%
EL1-01-2/2-R	HI-27/30/35/40	Lutron	Diva	DVSTV-XX	120	0-10v	Wallbox	High & Low-End Trim Required		100.0%	0.7%
EL1-01-2/2-R	WD-5/6/7									100.0%	0.7%
EL1-01-2/2-R	HI-27/30/35/40	Lutron	Nova T	NTSTV-DV-XX	120	0-10v	Wallbox	High & Low-End Trim Required		100.0%	0.9%
EL1-01-2/2-R	WD-5/6/7									100.0%	0.6%

Dimmer compatibility testing performed using 120V/60Hz supply.
Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.
The design, specification, or performance of compatible dimmers is subject to change without notice.
0-10V dimming options are configured for linear control.
For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93804-01-3 - 11/2026

DIMMER COMPATIBILITY
200 SERIES
DRIVER MODELS: EL2-2, EL2-2-R, EL2-01-2, EL2-01-2-R
LED MODELS: HI-27/30/35/40, WD-5/6/7

www.8lighting.com

No.8 Lighting Driver Model	No.8 Lighting LED Model	Dimmer Manufacturer	Dimmer Model/Family	Dimmer Model Tested	Voltage	Dimmer Type	Product Type	Reccomended Trim Settings		Dimming Range	
								High-End (%)	Low-End (%)	High-End (%)	Low-End (%)
EL2-2, EL2-2-R											
EL2/2-R-2/2-R*	HI-27/30/35/40	Lutron	Homeworks QSX	LQSE-1DAL2-D	120	DALI	Residential/ Commercial System	100.0	1.0	**100.0%**	**1.0%**
EL2/2-R-2/2-R*	WD-5/6/7							100.0	1.0	**100.0%**	**0.6%**
EL2-01-2, EL2-01-2-R											
EL2/2-R-01-2/2-R*	HI-27/30/35/40	Lutron	Homeworks QSX	LQSE-1DAL2-D	120	DALI	Residential/ Commercial System	100.0	1.0	**100.0%**	**0.1%**
EL2/2-R-01-2/2-R*	WD-5/6/7							100.0	1.0	**100.0%**	**0.1%**

Dimmer compatibility testing performed using 120V/60Hz supply.
Variations in supply power may require adjustments to recommended trim settings and/or affect dimming performance.
The design, specification, or performance of compatible dimmers is subject to change without notice.
***To minimize asynchronous behavior with Lutron LQSE-1DAL2-D module, limit the number of zones per DALI bus to a maximum of eight (8) per room.**
DALI dimming options are configured for logarithmic control.
For questions regarding the compatibility of dimmer models not listed above, please contact Number Eight Lighting customer service at (707) 794-0888.

93804-01-4 - 11/2026